

Contents

001		
1 1.1 1.2 1.3 1.4 1.5 1.6 1.7	Appliance at a glance	3 3334444
2	General safety instructions	4
3 3.1 3.2 3.3	Functionality of the Touch display Navigation and symbol explanation Menus Sleep mode	6 6 7
4 4.1 4.2	Putting into operation Switching on appliance (first use) Starting the EasyTwist-Ice for the first time*	7 7 7
5 5.1 5.2 5.3 5.4 5.5	Storage Information regarding storage Fridge compartment BioFresh Freezer compartment Storage times	8 8 8 8 9
6	5 57	10
7 7.1 7.1.1 7.1.2 7.2 7.2.1	Controls and displays Status display Display symbols	LO LO LO
7.2.3	Switching temperature zones off and on WiFi	
ໍ 5 ເ	Temperature	
°C⁄ F	Temperature unit	
D1	D-Value	
*	SuperCool	
**	SuperFrost	
	PartyMode	
<u>×</u>	HolidayMode	
Ψ	SabbathMode	
\mathbb{Q}	E-Saver	
$\langle O \rangle$	Display brightness	
	Door alarm	
		-0

×fm	Input lock	15
Service Noc Nockel Index: Service:	Info	16
Σ	Reminder	. 16
\bigcirc	Demo mode	. 16
(5	Reset	17
7.3 7.3.1 7.3.2	Fault messages Warnings Message	
8	Features	17
8.1	4-star freezer compartment	17
8.2	Door rack	18
8.3 8.4	Shelves Dividing shelf	18 18
8.5	VarioSafe*	18
8.6	Adjustable bottle shelf	21
8.7	Drawers	21
8.8 8.9	Fruit & Vegetable safe cover	22
8.9 8.10	Adjusting the moisture levels Glass shelves	22 23
8.11	EasyTwist-Ice*	23
8.12	VarioSpace	24
8.13	Bottle holder	24
8.14	Freezer pack	24
9	Maintenance	25
9.1	FreshAir carbon filter	25
9.2 9.3	Disassembling / assembling pull-out systems Defrosting the appliance	25 25
9.4	Cleaning the appliance	25
10	Customer help	28
10.1	Technical specifications	28
10.2	Operating noises	28
10.3	Technical fault	28
10.4	Customer Service	30
10.5	Model plate	30
11	Shutting down	30
12	Disposal	30
12.1	Preparing appliance for disposal	30
12.2	Disposing of the appliance in an environmentally	70
	friendly manner	30

The manufacturer is continually working on the further development of all types and models. Please be aware that we reserve the right to make changes to the shape, equip-ment and technology.



Read instructions

Explanation

Please read the information in these instructions carefully to understand all of the benefits of your new appliance.

Symbol	Explanation	1.2 Overview of the appliance and
	Full instructions on the internet	features
C	You can find detailed instructions on the internet using the QR code on the front of these instruction or by entering the service number at home.liebherr.com/fridge-manuals. The service number can be found on the serial tag:	
	Check appliance Check all parts for transport damage. If you have any complaints, please contact your agent or customer service.	
*	Differences These instructions apply to a range of models, so differences are possible. Sections that apply to certain models only are marked with an asterisk (*).	
/	Instructions and results	Fig. 1 Example illustration
	Instructions are marked with a \blacktriangleright .	Temperature range
	Results are marked with a \triangleright .	 (A) Fridge compartment (B) BioFresh (C) Freezer compartment (D) Coldest zone
	Videos	Features
	Videos about the appliances are available on the YouTube channels of Liebherr-Hausgeräte.	 (1) Transport handles (10) Meat & Dairy-Safe* (2) Controls (11) Outlet (12) Freezer compartmen
These oper	ating instructions apply to:	vated charcoal filter
CBN 5	52(i) / 57(v)(i)	 (4) Dry rear wall (13) Serial tag (5) Separable storage (14) EasyTwist-Ice*
	572i	shelf
		(6) Storage shelf (15) Can rack
Note If your app	liance has an N in its appliance designation, it is	 (7) Adjustable bottle shelf (16) Bottle rack (17) Bottle holder

If your appliance has an N in its appliance designation, it is a NoFrost appliance.

1 Appliance at a glance

1.1 Scope of delivery

Check all parts for transport damage. Contact your dealer or customer service in the event of complaints. (see 10.4 Customer Service)

Your new appliance comes with the following parts:

- Standalone appliance
- Features (depending on the model)
- Installation materials (depending on the model)
- "Quick Start Guide"
- "Installation Guide"
- Service Brochure

Note

Shelves, drawers and baskets are arranged for optimum energy efficiency when the appliance is delivered. Changing how the shelves, for example, are inserted in the fridge compartment does not have any impact on energy consumption.

(18) Adjustable feet (front)

1.3 SmartDevice

table-Safe

(9) Fruit & Vegetable-Safe

SmartDevice is the networking solution for your fridgefreezer.

If your appliance SmartDevice-enabled or compatible, you can quickly and easily connect your appliance to your WiFi. With the SmartDevice app, you can operate your appliance from a mobile device. Additional functions and setting options are available in the SmartDevice SmartDevice app.

SmartDevic	e-	Your appliance is capable of being a
enabled	appli-	SmartDevice. To be able to connect
ance:*		your device to WiFi, you need to
		download the SmartDevice app.*

General safety instructions

SmartDeviceance:*

Your appliance is compatible for use compatible appli- with the SmartDeviceBox. You must first purchase and install the Smart-DeviceBox. In order to connect your appliance to the WiFi, you need to download the SmartDevice app.*



information smartdevice.liebherr.com More about SmartDevice:

the home.liebherr.com/shop/de/deu/

Purchasing SmartDeviceBox in the Liebherr-Hausgeräte store:*

smartdevicebox.html*

Downloading the SmartDevice app:



After installing and configuring the SmartDevice, you can connect your appliance to the WiFi using the SmartDevice app and the WiFi appliance function (see WiFi).

Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan.

You cannot use the SmartDeviceBox.*

1.4 Appliance range of use

Intended use

The appliance is only suitable for cooling food products in a domestic or household-like environment. This includes, for example, use:

- in staff kitchens, bed and breakfast establishments.
- by guests in country houses, hotels, motels and other accommodation,
- for catering and similar services in the wholesale trade.

The appliance is not suitable as a built-in unit.

All other types of use are not permitted.

Foreseeable misuse

The following applications are expressly forbidden:

- Storing and refrigerating medicines, blood plasma, laboratory preparations or similar substances and products based on the Medical Device Directive 2007/47/EC
- Use in areas at risk of explosions

Misusing the appliance may lead to damage to the goods stored or they may spoil.

Climate classifications

Depending on the climate classification the appliance is designed to operate in restricted ambient temperatures. The climate classification applying to your appliance is printed on the rating plate.

Note

Keep to the specified ambient temperatures in order to guarantee that the appliance works properly.

Climate clas- sification	for ambient temperatures of
SN	10 °C to 32 °C
N	16 °C to 32 °C
ST	16 °C to 38 °C
Т	16 °C to 43 °C
SN-ST	10 °C to 38 °C
SN-T	10 °C to 43 °C

1.5 Conformity

The refrigerant circuit has been tested for leaks. The appliance complies with the applicable safety regulations and with the corresponding directives.

For marke ^t	the t:*	EU	The appliance complies with directive 2014/53/EU.*
For market		GΒ	The appliance complies with Radio Equipment Regulations 2017 SI 2017 No. 1206.*

The full text of the EU Declaration of Conformity is available on the following website: www.Liebherr.com

The BioFresh compartment meets the requirements of a cold storage compartment as set out in DIN EN 62552:2020.

1.6 SVHC substances according to **REACH** regulation

You can check whether your appliance contains SVHC substances according to RÉACH regulation at the following link: home.liebherr.com/de/deu/de/liebherr-erleben/nachhaltigkeit/umwelt/scip/scip.html

1.7 EPREL database

Details about energy labelling and ecodesign requirements will be available on the European product database (EPREL) from 1st March 2021. You can access the product database at the following link: https://eprel.ec.europa.eu/ You will be asked to enter the model ID. You can find the model ID on the nameplate.

2 General safety instructions

Please keep these operating instructions in a safe place so you can refer back to them at any time.

If you pass the appliance on, please hand these operating instructions to the next user.

Read these operating instructions carefully before use to ensure safe and correct use of the appliance. Follow the instructions, safety instructions and warning messages included at all times. They are important for ensuring you can operate and install the appliance safely and without any problems.

Danger for the user:

- This device can be used by children and people with impaired physical, sensory or mental abilities or with a lack of experience and knowledge provided that they are supervised or have received instruction in the safe use of this device, and about the resulting hazards. Children must not play with this appliance. Cleaning and user maintenance work must not be carried out by children without adult supervision. Children aged between 3 and 8 are allowed to load and unload the appliance. Children below the age of 3 must be kept away from the appliance unless they are under continuous adult supervision.
- The socket must be easily accessible so that the appliance can be disconnected quickly from the electricity in an emergency. It must not be located in the area behind the appliance.
- When disconnecting the appliance from the supply, always take hold of the plug. Do not pull the cable.
- In the event of a fault pull out the mains plug or deactivate the fuse.
- Do not damage the mains power cable. Do not operate the appliance with a defective mains power cable.
- Only customer service or other specially trained staff may repair or perform other operations on the appliance.
- Only assemble, connect and dispose of the appliance according to the instructions.
- The manufacturer is not liable for damage caused by a faulty fixed water connection.

Fire hazard:

- The coolant used (information on the model plate) is ecofriendly but also flammable. Any leaking coolant may ignite.
 - Do not damage the refrigerant circuit pipes.
 - Do not handle ignition sources inside the appliance.

- Do not use electrical appliances inside the appliance (e.g. steam cleaners, heaters, ice cream makers, etc.).
- If the refrigerant leaks: remove any naked flames or ignition sources from the vicinity of the leakage point. Properly air the room. Inform customer services.
- Do not store explosives or sprays using combustible propellants such as butane, propane, pentane, etc. in the appliance. To identify these spray cans, look for the list of contents printed on the can, or a flame symbol. Gases possibly escaping may ignite due to electrical components.
- Keep burning candles, lamps and other items with naked flames away from the appliance so that they do not set the appliance on fire.
- Please be sure to store alcoholic drinks or other packaging containing alcohol in tightly closed containers. Any alcohol that leaks out may be ignited by electrical components.

Danger of tipping and falling:

- Do not misuse the plinth, drawers, doors etc. as a step or for support. This applies particularly to children.

Danger of food poisoning:

- Do not consume food which has been stored too long.

Danger of frostbite, numbness and pain:

 Avoid prolonged skin contact with cold surfaces or refrigerated/frozen goods or take protective measures, e.g wear gloves.

Danger of injury and damage:

- Hot steam can lead to injury. Do not use electrical heating or steam cleaning equipment, open flames or defrosting sprays to defrost.
- Do not use sharp implements to remove the ice.

Risk of crushing:

Do not hold the hinge when opening and closing the door. Fingers may get caught.

Symbols on the appliance:



This symbol may be located on the compressor. It relates to the oil in the compressor and makes reference to the risk that: Swallowing or inhaling can be fatal. This advice is only relevant to recycling. There is no danger in normal operation.

Functionality of the Touch display



This symbol is located on the compressor and indicates the danger of flammable materials. Do not remove the sticker.

This or a similar sticker may be located on the rear of the appliance. This sticker indicates that there are vacuum insulation panels (VIP) or perlite panels in the door and/or housing. This advice is only relevant to recycling. Do not remove the sticker.

Please note the warning messages and other specific advice in the other chapters:

DANGER	indicates an immediately hazardous situation which will lead to death or serious injuries if it is not avoided.
WARNING	indicates a hazardous situation which may lead to death or serious injuries if it is not avoided.
CAUTION	indicates a hazardous situation which may lead to minor or moderate injuries if it is not avoided.
NOTICE	indicates a hazardous situation which may lead to damage to property if it is not avoided.
Note	indicates useful instructions and tips.

3 Functionality of the Touch display

You operate your appliance using the Touch display. You select appliance functions in the Touch display (hereafter referred to as display) by tapping them. If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher-level menu or directly to the status display.

3.1 Navigation and symbol explanation

In the illustrations, different symbols are used to navigate the display. The following table describes these symbols.

Symbol	Description
	Press the Next navigation arrow: Navigates to the next option in the menu.
	Press the Back navigation arrow: Jumps back one option in the menu.

Symbol	Description
	Press the navigation arrow several times in succession:
	Navigates in the menu to the desired function.
	Press the Confirm symbol: Activates/deactivates func- tion. Opens submenu.
Back	Press the Confirm symbol together with the back icon: Jumps back one menu level.
♥ ©	Arrow with clock: It takes more than 10 seconds for the following message to appear in the display.
	Arrow with a time indication: It takes the specified amount of time until the following message appears in the display.
	"Open Settings menu" symbol: Navigates to the Settings menu and opens the settings menu.
	If necessary: Navigate to the desired function in the Settings menu.
	(see 3.2.1 Opening the Settings menu)
	"Open Advanced menu" symbol:
	Navigates to the Advancec menu and opens the advanced menu.
	If necessary: Navigate to the desired function in the Advanced menu.
	(see 3.2.2 Opening the Advanced menu)
No action for 10 seconds	If you do not perform any action on the display for 10 seconds, the display either jumps back to the higher- level menu or directly to the status display.
Opening door and closing it again	If you open the door and immediately close it again the display jumps directly back to the status display.

Note: Illustrations of the display are shown in the English version.

3.2 Menus

The appliance functions can be found in various menus.

Menu	Description
Main menu	When you switch the appliance on, you are automatically in the main menu.
	From here you can navigate to the most important appliance functions, to the Settings menu and to the Advanced menu.
ک Settings	The Settings menu contains additional appliance functions for setting up your appliance. (see 3.2.1 Opening the Settings menu)
Settings menu	
Advanced menu	The advanced menu contains special appli- ance functions for setting up your appli- ance. Access to the Advanced menu is protected by the numerical code 151 . (see 3.2.2 Opening the Advanced menu)

3.2.1 Opening the Settings menu





Fig. 2 Example illustration

- Carry out action steps according to the illustration.
- ▷ Settings menu is open.
- If necessary: Navigate to the desired function.

3.2.2 Opening the Advanced menu






Fig. 4 Example illustration, access with numerical code 151
Carry out action steps according to the illustration.

▷ The expanded menu is open.

If necessary: Navigate to the desired function.

3.3 Sleep mode

If you do not touch the display for 1 minute, the display switches to sleep mode. In sleep mode, the display brightness is dimmed.

3.3.1 Ending sleep mode

Press any navigation key.

 \triangleright Sleep mode is ended.

4 Putting into operation

4.1 Switching on appliance (first use)

Make sure that the following requirements are fulfilled:

- □ The appliance has been installed and connected in accordance with the installation instructions.
- □ All adhesive strips, adhesive and protective films and transport locks are removed from inside and on the appliance.
- □ All marketing leaflets are removed from the drawers.
- □ You are familiar with the functionality of the Touch display. (see 3 Functionality of the Touch display)
- Switch on the appliance using the Touch display:




Fig. 5 Example illustration

- \triangleright The status display appears.
- The appliance cools to the temperature set at the factory.
 The appliance starts in demo mode (status display with DEMO appears): If the appliance starts in demo mode, you can deactivate demo mode within the next 5 minutes. (see Demo mode)

More information:

- Start the EasyTwist-Ice for the first time. (see 4.2 Starting the EasyTwist-Ice for the first time*) *
- Start the SmartDevice for the first time. (see 1.3 Smart-Device) and (see WiFi)

Note

The manufacturer recommends:

- Stock with food: Wait for around 6 hours until the set temperature is reached.
- **Store frozen foods** at -18 °C or colder.
- Store frozen foods at -18 °C or colder.
- Observe the notes on storing food. (see 5.1 Information regarding storage)

Note

Accessories can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/ zubehor.html.

4.2 Starting the EasyTwist-Ice for the first time*

If your appliance is equipped with EasyTwist-Ice, you must clean the EasyTwist-Ice **before using it for the first time**.

Make sure that the following requirements are fulfilled:

- The appliance is properly connected.
- Clean the EasyTwist-Ice. (see 9.4.5 Cleaning the Easy-Twist-Ice)

▶ Fill the water tank.

5 Storage

5.1 Information regarding storage

Risk of fire

Do not use any electrical appliances in the food area of the appliance unless recommended by the manufacturer.

Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient. ► Always keep air slots clear.

- Observe the following specifications for storage:
- Keep the air vents on the inside of the rear wall free.
- In the freezer compartment: Package food properly.
- In the freezer compartment: Package food properly.
- Package or cover foods that readily take on or give off odours or taste in closed containers.
- Package raw meat or fish in clean, closed containers. This will prevent meat or fish from touching or dripping onto other food.
- Keep liquids in closed containers.
- Leave space between goods to ensure good air circulation.
- Store food according to the instructions on the packaging.
- Always observe the best-before date indicated on the packaging.

Note

Failure to follow these guidelines can lead to foodstuffs spoiling.

5.2 Fridge compartment

The air circulation in the appliance creates different temperature zones. You will find the different temperature zones in the appliance and equipment overview. (see 1.2 Overview of the appliance and features)

5.2.1 Arranging your food properly

- Upper area and door: Store butter, cheese, tinned food and tubes.
- Coldest temperature zone: Store perishable foods such as pre-cooked meals.

5.3 BioFresh

BioFresh will extend the storage time for some fresh foods compared to traditional refrigeration.

Note

- If the temperature drops below 0 °C foods may freeze.
- Store cold-sensitive produce such as cucumbers, aubergines, courgettes and tropical fruit in the fridge compartment.

5.3.1 Fruit & Vegetable safe 🖒 🥖 🚳

This safe creates a storage climate of close to 0 °C. The tight lid ensures constant levels of humidity. This storage climate is suitable for storing unpackaged food with high intrinsic moisture (for example, lettuce, vegetables, fruit).

The humidity in the compartment depends on the moisture content of the chilled goods placed in it, and also depends on how often the compartment is opened. You can regulate the humidity level. (see 8.9 Adjusting the moisture levels)

Arranging your food properly

- Store unpackaged fruit and vegetables. If the humidity is too high:
- Regulate the humidity. (see 8.9 Adjusting the moisture levels)

5.3.2 Meat & Dairy safe 🖉 🔎 🗇

This safe creates a storage climate of close to 0 °C. This storage climate is suitable for more sensitive foods (e.g. dairy products, meat, fish, sausage).

Arranging your food properly

Store dry or packaged food.

5.4 Freezer compartment

Here, a dry, frosty storage climate is created at -18 °C. The frosty storage climate is suitable for storing frozen food for several months, for making ice cubes or freezing fresh food.

5.4.1 Freezing food

Freezing quantity

The maximum amount of fresh food that you can freeze within 24 hours is specified on the type plate (see 10.5 Model plate) under "Freezing capacity ... kg/24h".

To ensure that food quickly freezes through, adhere to the following quantities per package:

- Fruit and vegetables up to 1 kg
- Meat up to 2.5 kg

Freezing food using SuperFrost


Depending on the quantity to be frozen, you can activate SuperFrost before freezing in order to achieve lower freezing temperatures. (see SuperFrost)

► Activate SuperFrost if the amount of food you have to freeze is more than approx. 2 kg.

The time at which you activate SuperFrost depends on the amount of food you have to freeze:

Freezing quan- tity	Time at which you should activate SuperFrost
Small amount of food to freeze	Activate SuperFrost about 6 hours before freezing.
	You can place the food in the freezer as soon as the appliance automatically deactivates SuperFrost.
	Activate SuperFrost about 24 hours before freezing.
to freeze	You can place the food in the freezer as soon as the appliance automatically deactivates SuperFrost.

Arranging your food properly



Risk of injury from broken glass! Bottles and cans with beverages can burst during freezing. This applies in particular to carbonated beverages.

Only freeze bottles and cans with beverages if you have activated the BottleTimer function in the SmartDevice app.

Freezing quan- tity	Arranging your food properly
Small amount of food to freeze	Place packaged food in the top drawer. If possible, place groceries at the back of the drawer near the rear wall.
Maximum amount of food to freeze	Distribute packaged groceries throughout all drawers, but do not place any groceries in the bottom drawer. If possible, place groceries at the back of the drawer near the rear wall.

5.4.2 Defrosting food



Risk of food poisoning!

- Do not re-freeze thawed food.
- ► Use defrosted foodstuff as soon as possible.

You can defrost food in several ways:

- In the fridge compartment
- In the microwave
- In the oven/fan-assisted oven
- At room temperature
- ▶ Take out only as much food as necessary.

5.5 Storage times

Refer to the specified storage times as a guide. In the case of foods with a minimum shelf life, the date indicated on the packaging still applies.

5.5.1 Fridge section

Always follow the best-before date stated on the packaging.

5.5.2 BioFresh

Recommended storage periods in the Meat & Dairy-Safe		
Butter	at 1 °C	up to 90 days
Hard cheese	at 1 °C	up to 110 days
Milk	at 1 °C	up to 12 days
Sausage, cold meats	at 1 °C	up to 8 days
Poultry	at 1 °C	up to 6 days
Pork	at 1 °C	up to 6 days
Beef	at 1 °C	up to 6 days
Game	atl°C	up to 6 days

Note

Remember that high-protein foods perish quicker; shellfish and crustaceans do not last as long as fish, and fish does not last as long as meat.

Recommended storage periods in the Fruit & Vegetable- Safe		
Vegetables, salads		
Artichokes	at 1 °C	up to 14 days
Celery	at 1 °C	up to 28 days
Cauliflower	at 1 °C	up to 21 days
Broccoli	atl°C	up to 13 days

Recommended storage periods in the Fruit & Vegetable-Safe		
Chicory	atl°C	up to 27 days
Lettuce	atl°C	up to 19 days
Peas	atl°C	up to 14 days
Kale	at 1 °C	up to 14 days
Carrots	at 1 °C	up to 80 days
Garlic	at 1 °C	up to 160 days
Turnip	at 1 °C	up to 14 days
Lettuce	atl°C	up to 13 days
Herbs	at 1 °C	up to 13 days
Leeks	atl°C	up to 29 days
Mushrooms	atl°C	up to 7 days
Radishes	at 1 °C	up to 10 days
Brussels sprouts	atl°C	up to 20 days
Asparagus	atl°C	up to 18 days
Spinach	atl°C	up to 13 days
Savoy	atl°C	up to 20 days
Fruit		
Apricots	atl°C	up to 13 days
Apples	atl°C	up to 80 days
Pears	at 1 °C	up to 55 days
Blackberries	atl°C	up to 3 days
Dates	at 1 °C	up to 180 days
Strawberries	at 1 °C	up to 7 days
Figs	atl°C	up to 7 days
Blueberries	at 1 °C	up to 9 days
Raspberries	at 1 °C	up to 3 days
Currants	atl°C	up to 7 days
Sweet cherries	at 1 °C	up to 14 days
Kiwis	atl°C	up to 80 days
Peaches	atl°C	up to 13 days
Plums	atl°C	up to 20 days
Cranberries	atl°C	up to 60 days
Rhubarb	atl°C	up to 13 days
Gooseberries	atl°C	up to 13 days
Grapes	atl°C	up to 29 days

5.5.3 Freezer compartment

Recommended storage period for various types of food		
Ice cream	at -18 °C	2 to 6 months
Sausages, ham	at -18 °C	2 to 3 months
Bread, baked goods	at -18 °C	2 to 6 months
Game, pork	at -18 °C	6 to 9 months
Fatty fish	at -18 °C	2 to 6 months
Lean fish	at -18 °C	6 to 8 months

	Recommended storage period for various types of food			
	Cheese at -18 °C 2 to 6 months			
Poultry, beef at -18 °C 6 to 12 months		6 to 12 months		
	Vegetables, fruit	at -18 °C	6 to 12 months	

6 Saving energy

- Pay attention to good ventilation. Do not cover ventilation holes or grids.
- Always keep the fan air slits clear.
- Do not install the appliance in direct sunlight, next to an oven, radiator or similar.
- Energy consumption depends on the installation conditions, e.g. the ambient temperature (see 1.4 Appliance range of use) . A warmer ambient temperature can increase the energy consumption.
- Open the appliance for as short a time as possible.
- The lower the temperature is set the higher the energy consumption.
- Sort your food: home.liebherr.com/food.
- Keep all food properly packed and covered. This prevents frost from forming.
- Only take food out for as long as necessary so that it doesn't warm up too much.
- Inserting warm food: allow to cool down to room temperature first.
- Thaw frozen food in the refrigerator.
- For longer periods of absence, use HolidayMode (see HolidayMode).

Dust deposits increase energy consumption:

For refrigerators with heat exchangers dust the metal grid on the back of the appliance once a year.

7 Controls

7.1 Controls and displays

7.1.1 Status display




Fig. 6

- (1) Temperature display of the fridge section
- (2) Freezer compartment temperature display

The Status display shows the set temperature and is the home display. From there, you can navigate to the options and settings.

7.1.2 Display symbols

Display symbols provide information on the current appliance status:

Symbol	Appliance status
$(\begin{tabular}{c} \begin{tabular}{c} \end{tabular}$	Standby The appliance or temperature zone is switched off.

Symbol Appliance status

Flashing number

Appliance is working. Temperature flashes until the set value is reached.



Flashing symbol

Appliance is working. Setting is made.

Bar grows steadily

Function is activated.

7.2 Appliance functions

7.2.1 Notes on the appliance functions

The appliance functions are set at the factory so that your appliance is fully functional.

Before you alter, activate or deactivate the device functions, make sure that the following requirements are met:

- □ You have read and understood the descriptions of how the display works.
- $\hfill\square$ You have familiarised yourself with the operating and display elements of your appliance.




Turn off appliance

This setting turns off the whole appliance.

Switching off the entire appliance



Fig. 7



Fia. 8

 \triangleright Off: Display goes black.

7.2.3 Switching temperature zones off and on

You can switch temperature zones of the appliance off independently.

Application:

- Cleaning
- Defrosting

Switching the fridge compartment off

Make sure that the following requirements are fulfilled: Refrigerator compartment has been emptied.

Controls




Fig. 9 Example illustration

• Carry out action steps according to the illustration.

▷ Refrigerator compartment is switched off.

Switching the fridge compartment on




Fig. 10 Example illustration

- Carry out action steps according to the illustration.
- ▷ Refrigerator compartment is switched on.
- \triangleright The appliance cools to the last set temperature.



Use this function to connect your appliance to WiFi. You can then operate it via the SmartDevice app on a mobile device. You can also use this function to disconnect or reset the WiFi connection.

To connect your device to WiFi, you need the SmartDeviceBox.*

More information on the SmartDevice: (see 1.3 SmartDevice)

Note

The SmartDevice function is not available in the following countries: Russia, Belarus, Kazakhstan.

You cannot use the SmartDeviceBox.*

Establishing the WiFi connection for the first time

Make sure that the following requirements are fulfilled:

- □ You have purchased and inserted a SmartDeviceBox. (see 1.3 SmartDevice) *
- You have installed the SmartDevice app (see apps.home.liebherr.com).
- Registration in the SmartDevice app is completed.



Fig. 11




Fig. 12

- Carry out action steps according to the illustration.
- > Connection is established.

Disconnecting from the WiFi




Fig. 13




Fig. 14

- Carry out action steps according to the illustration.
- \triangleright There is no connection.

Resetting the WiFi connection



Fig. 15






Fig. 16

- Carry out action steps according to the illustration.
- WiFi connection and other WiFi settings are reset to factory settings.

Showing information about the WiFi connection







• Carry out action steps according to the illustration.

⁵ [°] Temperature

Use this function to set the temperature.

The temperature depends on the following factors:

- How often the door is opened
- How long the door is open for
- The room temperature of the installation site
- The type, temperature and amount of food

Temperature zone

BioFresh

Recommended setting



Fridge compart- 5 °C

-18 c

Freezer compart- -18 °C

ment

0

(see Setting the temperature in the BioFresh)

Setting the temperature in the fridge compartment




Fig. 19

- Carry out action steps according to the illustration.
- ▷ Temperature is set.

Setting the temperature in the freezer compartment




Fig. 20

Carry out action steps according to the illustration.
 Temperature is set.

Setting the temperature in the BioFresh

You can set the temperature using the **BioFresh B-Value** in the customer menu.



Use this function to set the temperature unit. You can set degrees Celsius or degrees Fahrenheit as the temperature unit.

Setting the temperature unit



Fig. 21




Fig. 22 Example illustration: Switch from degrees Celsius to degrees Fahrenheit.

- Carry out action steps according to the illustration.
- \triangleright The temperature unit is set.

When delivered, the temperature in the BioFresh compartment is set to **B5**. The status indicator on the display shows the target temperature in the BioFresh.

You can change this value slightly if a higher or lower ambient temperature makes it necessary. When setting the value, note:

Value	Description
B1	Lowest temperature
B1-B4	The temperature can drop below 0 °C which means foods can easily freeze.

Value	Description
B5	Pre-set temperature
B9	Highest temperature
BioFresh B-Value	

Selecting the setting

Set value in customer menu .

D1 _{D-Value}

The D-Value is pre-set for your appliance and is not permitted to be changed.

* SuperCool

This function selects the lowest cooling temperature. This gives you colder storage temperatures.

This function is relevant to the fridge section Fig. 1 (A)

Use:

- Cool large amounts of food quickly.

Activating/deactivating the function

- Using the fridge section: activate the function when you add the goods.
- Activating/deactivating.
- -or-
- Activate/deactivate using the SmartDevice app.*

The function automatically turns off. The appliance goes back to normal mode. The temperature adjusts itself to the set level.

This function selects the lowest freezing temperature. This gives you colder storage temperatures.

This function refers to the freezer section Fig. 1 (C).

Use:

- For storing more than 2 kg fresh food every day.
- Freezing fresh food quickly to the core.
- Increasing the cold reserves in the stored goods before defrosting the appliance.

Activating/deactivating the function

- With a small amount to freeze:
- Activate 6 hours before use.
- With a maximum amount to freeze:
- Activate 24 hours before use.
- Activating/deactivating.
- -or-
- Activate/deactivate using the SmartDevice app.*

The function automatically turns off. The appliance goes back to normal mode. The temperature adjusts itself to the set level.

PartyMode

You can use this function to activate or deactivate Party-Mode. PartyMode activates various functions that are useful for a party. PartyMode activates the following functions:

- SuperCool (see SuperCool)
- SuperFrost (see SuperFrost)

You can adjust all listed functions individually and flexibly. When you deactivate PartyMode, all changes are discarded.

Activating PartyMode








Fig. 24

- ► Carry out action steps according to the illustration.
- PartyMode and the associated functions are activated.
 The current temperature flashes until the target tempera-

Deactivating PartyMode

ture is reached.

The PartyMode is automatically deactivated after 24 seconds. However, you can also deactivate PartyMode manually at any time:



Fig. 25




Fig. 26

- Carry out action steps according to the illustration.
- ▷ PartyMode is deactivated.
- The appliance cools to the temperature set previously: The current temperature flashes until the target temperature is reached.

HolidayMode

This function minimises the energy consumption during an extended absence. The temperature of the refrigerator compartment is set to 15 °C and this is displayed on the status screen when the temperature has been reached.

The set freezer temperature remains unchanged.

This function refers to the fridge section Fig. 1 (A).

Use:

- Save energy if you plan to be away for a while.
- Avoid coming home to bad smells and mould.

Activating/deactivating the function

- Empty everything from the fridge section.
- Activating/deactivating.

▷ On: Fridge temperature is raised.

 \triangleright Off: the previously set temperature is restored.

You can use this function to activate or deactivate SabbathMode. If you activate this function, some electronic functions are switched off. As a result, your device meets the religious requirements for Jewish holidays such as Sabbath and complies with STAR-K Kosher certification.

Device status when SabbathMode is active

The status display shows SabbathMode permanently.

All functions on the display are locked except for the **Deactivate SabbathMode function**.

Active functions remain active.

The display remains bright when you close the door.

The interior lighting is deactivated.

Reminders are not implemented. The set time interval stops.

Reminders and warnings are not displayed.

There is no door alarm.

There is no temperature alarm.

The defrosting cycle operates only for the specified time, without considering the device consumption.

After a power failure, the device returns to SabbathMode.

Device status

Note

This appliance has certification from the "Institute for Science and Halacha". (www.machonhalacha.co.il)

You can find a list of STAR-K-certified appliances at www.star-k.org/appliances.

Activating SabbathMode

Danger of food poisoning from spoiled food!

If you have SabbathMode activated and a power failure occurs, no message appears in the status display about the power failure. Once the power is restored, the appliance continues to operate in SabbathMode. The power failure may mean that food spoils and the consumption of this food could lead to food poisoning.

After a power failure:

- Do not consume food that was frozen and has thawed out.
- ► Call the settings menu.
- Press the navigation arrow repeatedly until the corresponding function is displayed.




Fig. 27

- Carry out action steps according to the illustration.
- ▷ SabbathMode is activated.
- Dash The status display shows SabbathMode permanently.

Deactivating SabbathMode

The SabbathMode is automatically deactivated after 80 hours. However, you can also deactivate SabbathMode manually at any time:



Fig. 28

- Carry out action steps according to the illustration.
- ▷ SabbathMode is deactivated.



This function activates or deactivates the energy-saving mode. When you activate this function, the energy consumption decreases and the temperature increases by 2 °C in the appliance. The food remains fresh, but the shelf life is shortened.

Temperature zone	Recommended setting (see Temperature)	Temperature when E-Saver activated
5 c Fridge compart- ment	5 °C	7 °C
-18 ° Freezer compartment	-18 °C	-16 °C

Temperatures

Activating E-Saver

 Tap navigation arrow repeatedly until corresponding function is displayed.



Fig. 29

- ► Carry out action steps according to the illustration.
- ▷ Energy-saving mode is activated.

Deactivating E-Saver

 Tap navigation arrow repeatedly until corresponding function is displayed.



Fig. 30

- Carry out action steps according to the illustration.
- ▷ Energy-saving mode is deactivated.

CleaningMode

You can use this function to activate or deactivate Cleaning-Mode. CleaningMode enables the appliance to be cleaned conveniently.

This setting applies to the fridge section.

Application:

- Clean the fridge section. (see 9.4 Cleaning the appliance)

Device status when CleaningMode is active

The status display shows CleaningMode permanently.

The fridge section is switched off.

The reminders and warnings are not displayed. No signal tone sounds

Device status

Activating CleaningMode



Fig. 31



Fig. 32

- Carry out action steps according to the illustration. ►
- \triangleright CleaningMode is activated.
- ▷ The status display shows CleaningMode permanently.

Deactivating CleaningMode

CleaningMode is deactivated automatically after 60 minutes. However, you can also deactivate Cleaning-Mode manually at any time:



- Fig. 33
- Carry out action steps according to the illustration.
- \triangleright CleaningMode is deactivated.
- \triangleright The appliance cools to the temperature set previously.

Display brightness

Use this function to set the display brightness in stages.

You can select the following brightness levels:

- 40 %
- 60 %
- 80 %
- 100 %

Setting the display brightness



- Fig. 35 Example illustration: Switch from 80 % to 60 %. Carry out action steps according to the illustration.
- ► \triangleright The display brightness is set.

Door alarm

Fig. 34

Set the time before the door alarm (see Close the door) sounds.

The options are as follows:

- 1 min
- 2 min
- 3 min
- Off -

Choose the setting

Set the time (see 7.3 Fault messages).



Input lock

You can use this function to activate or deactivate the input lock. The input lock prevents the appliance being operated accidentally, e.g. by children.

Application:

- Avoid unintentional modification of functions.
- Avoid unintentional switching off of the device.
- Avoid unintentional temperature setting. _

Activating the input lock

If you activate the input lock, you can continue to navigate in the menus but you cannot select or change other functions



Fig. 36




Fig. 37

- Carry out action steps according to the illustration.
- \triangleright Input lock is activated.

Deactivating the input lock

- Call the settings menu.
- ▶ Press the navigation arrow repeatedly until the corresponding function is displayed.

Controls



Fig. 38

- Carry out action steps according to the illustration.
- \triangleright Input lock is deactivated.



This setting allows the appliance information to be read out as well as access to the customer menu.

It provides the following information:

- Model name
- Index
- Serial number
- Service number

Show appliance data

- Tap the navigation arrows () repeatedly until the settings appear.
- Press Confirm ().
- Tap the navigation arrows () repeatedly until the information is displayed.
- Read the appliance info.

ر کبک Reminder

Reminders are given out acoustically by a beep and visually by a symbol in the display. The signal gets louder until the alert stops.



Replace FreshAir active carbon filter

This message appears when the air filter needs replacing.

- Change the air filter every six months.
- Confirm the message with OK.
- ▷ The service interval resets.
 ▷ The size filter successes the
- Dash The air filter guarantees the air quality in the fridge.

Activating the setting

Activating/deactivating.



Demo mode is a special feature for dealers who want to demonstrate appliance features. If you activate demo mode, all refrigeration functions are deactivated.

If you switch on your appliance and "Demo" appears in the status display, then demo mode is already activated.

If you activate and then deactivate demo mode, the appliance will be reset to factory defaults. (see Reset)

Activating demo mode



Fig. 39




Fig. 40

- ► Carry out action steps according to the illustration.
- \triangleright Demo mode is activated.
- \triangleright Appliance is switched off.
- Switch on the appliance. (see 4.1 Switching on appliance (first use))
 "DEMO" appears in the status display.

Deactivating demo mode



Fig. 41




Fig. 42

- Carry out action steps according to the illustration.
- \triangleright Demo mode is deactivated.
- \triangleright Appliance is switched off.
- Switch on the appliance. (see 4.1 Switching on appliance (first use))
- \triangleright Appliance is reset to factory settings.



This function resets all settings to the factory settings. All settings that you have made thus far will be reset to their original values.

Activating the setting

Activate .

7.3 Fault messages

Fault messages appear in the display. There are two categories of fault message:

Category	Meaning
Message	Reminder of general procedures. You can carry out these procedures to eliminate the message.
Warning	Appears when there are malfunctions. A signal sounds in addition to the display. The signal becomes louder until you acknowledge by tapping the display. You can eliminate simple defects yourself. For more serious defects, you must contact customer service.

7.3.1 Warnings



Close the door

This message appears if the door is open for too long.

You can set how long it takes for this message to appear . ▶ Stop alarm: Confirm the message.

- -or-
- Close the door.



Power cut

This message appears if the freezer temperature increased due to a power cut. After the power is restored, the appliance continues to work at the set temperature.

- Stop alarm: Confirm the message.
- > Temperature alert appears (see Temperature alarm) .

Temperature alarm

This message appears if the freezer temperature does not match the set temperature.

Variations in temperature could be because:

- Hot, fresh food was inserted.
- Too much warm room air flowed in when rearranging and removing food.
- The power was cut off for a while.
- The appliance is faulty.

When the fault is eliminated the appliance continues to work at the set temperature.

- Confirm the display.
- \triangleright The highest temperature is shown.
- Confirm display again.
- \triangleright The status display is displayed.
- ▷ The current temperature is shown.



This message appears if there is a fault with the appliance. An appliance component indicates a fault.

- Open the door.
- ▶ Note down the fault code.
- Confirm the message.
- \triangleright The signal tone stops.
- The status display appears.
 Close the door.
- Contact customer service. (see 10.4 Customer Service)

7.3.2 Message

Water tank


This message appears if there is not enough water in the water tank.

- Fill the water tank.
- The IceMaker produces ice cubes.
 When the water tank is full and the formation of the second se
- ▶ When the water tank is full and the following message appears: Check if the float is stuck.
- If necessary, drain the water and release the float with a thin object such as a cotton bud.
- When the water tank is full and the following message appears: Contact customer service. (see 10.4 Customer Service)

8 Features

8.1 4-star freezer compartment

8.1.1 Opening/closing the freezer compartment







Fig. 43

- Opening the freezer compartment:
- Reach into the handle area from below.
- ► Push the handle plate while pulling the door towards you. Closing the freezer compartment:
- Close the door while pushing from the front.
- \triangleright Door is engaged.

8.2 Door rack

8.2.1 Move/remove the door rack



- Fig. 44
- Slide the rack upwards.
- Pull forwards.
- Re-insert it in reverse order.

8.2.2 Disassembling the door rack

The door rack can be taken apart for cleaning.




Fig. 45

▶ Disassemble the door rack.

8.3 Shelves

8.3.1 Adjusting/removing the shelves

The shelves are prevented from being pulled out accidentally by pull out stops.




Fig. 46

- ▶ Lift the shelf and pull forward.
- \triangleright Line up the side runner.
- Adjust the height of the shelf: Lift or lower it to the desired height and slide it in.
 -or-

Fig. 47

- Remove the shelf completely: Pull it out to the front.
- Easier removal: Set the shelf at an angle.
- Insert the shelf again: Slide it in all the way.
- \triangleright The pull-out stoppers point downwards.
- \triangleright The pull-out stoppers are behind the front support.

8.4 Dividing shelf

8.4.1 Using the dividing shelf

The shelves are prevented from being pulled out accidentally by pull out stops.




Fig. 48 Push the dividing shelf underneath as shown.




Fig. 49

Adjusting the height:


- Pull the glass panels out Fig. 49 (1) from the front, one at a time.
- Release the support rails and click in at the height you want.
- Slide in the glass panels one at a time.
- Flat pull-out stoppers at the front, right behind the support rails.
- \triangleright High pull-out stoppers at the back.

Using both shelves:

- Hold the glass panel with one hand and pull it to the front.
- \triangleright The glass panel *Fig. 49 (1)* and trim strip are at the front.
- ▷ The stops *Fig. 49 (3)* point down.

8.5 VarioSafe*

The VarioSafe offers space in the refrigerator compartment for small groceries, packages, tubes and jars, for example.



(3) Recesses on the left and right side panel

Fig. 50

(1) VarioSafe drawer

(2) Side panels with ribs for VarioSafe drawer

8.5.1 Inserting the VarioSafe




Fig. 51

▶ Insert the VarioSafe into the refrigerator compartment at an angle *Fig. 51 (1)* until the recesses in the side *Fig. 51 (2)* of the VarioSafe are at the level of the support rib in the refrigerator compartment.




Fig. 52

- Set VarioSafe straight. *Fig. 52 (1)*
- ▶ Lift VarioSafe at the front. *Fig. 52 (2)*




Fig. 53

- ▶ Lift VarioSafe up toward the front.
- Push VarioSafe in to the rear.
- Lower VarioSafe.
- \triangleright VarioSafe audibly engages.
- ▷ VarioSafe is inserted.

8.5.2 Repositioning the VarioSafe

You can move the VarioSafe as a whole in the refrigerator compartment.





Fig. 54

► Lift VarioSafe at the front.





- ▶ Pull VarioSafe forwards until the recesses in the side of the VarioSafe are at the level of the support rib in the refrigerator compartment. *Fig. 55 (1)*
- Move VarioSafe up or down in the refrigerator compartment until the desired height is reached. Fig. 55 (2)




Fig. 56

- ► Lift VarioSafe at the front.
- Push VarioSafe in to the rear.
- VarioSafe audibly engages.
- ▷ VarioSafe is offset in height.

8.5.3 Moving the VarioSafe drawer

You can use the VarioSafe drawer at two different heights. If you would like to store taller foodstuffs in the VarioSafe drawer, slide the VarioSafe drawer in on the bottom rib. If you would like to store smaller foodstuffs in the VarioSafe drawer, slide the VarioSafe drawer in on the top rib.




Fig. 57

- ▶ Pull out the VarioSafe drawer as far as it will go.
- Lift the VarioSafe drawer up at the front.
- Remove the VarioSafe drawer to the front.




Fig. 58

- ► Lift the VarioSafe drawer up at the front.
- ▶ Place the VarioSafe drawer behind the stoppers on desired rib *Fig. 58 (1)* or *Fig. 58 (2)*.

▷ VarioSafe drawer is offset in height.

8.5.4 Removing the VarioSafe

You can remove the VarioSafe as a whole.




Fig. 59

► Lift VarioSafe at the front.




Fig. 60

Pull VarioSafe forwards Fig. 60 (1) until the recesses in the side of the VarioSafe are at the level of the support rib in the refrigerator compartment. Fig. 60 (2)




Fig. 61

- Set VarioSafe in refrigerator compartment at an angle. Fig. 61 (1)
- ► Take VarioSafe out to the front. *Fig. 61 (2)*
- \triangleright VarioSafe is removed.

8.5.5 Disassembling the VarioSafe

You can disassemble the VarioSafe into its individual parts if you want to clean the VarioSafe or if you need to install or remove parts.




Fig. 62

- Remove VarioSafe as a whole. (see 8.5.4 Removing the VarioSafe)
- ▶ Disassemble VarioSafe according to the illustration.

8.6 Adjustable bottle shelf

8.6.1 Using the bottle shelf

In the bottom of the fridge section you can either use the variable bottle shelf or the glass panel.




Fig. 63

- Remove the glass panel and store in a safe place.
- Lay bottles with their base towards the rear wall.

Note

If the bottles are protruding over the front of the bottle shelf:

Move the lower door rack up a place.

8.6.2 Removing the bottle shelf

- You can remove the bottle shelf for cleaning.
- ▶ Remove the glass panel above the bottle shelf.




Fig. 64

▶ Lift the bottle shelf at the front and pull out.

Note

Liebherr recommends the following:

Do not place any goods on the drawer cover below.

8.6.3 Inserting the bottle shelf




Fig. 65

Slide in the bottle shelf until it engages and push down.

8.7 Drawers

You can remove the drawers for cleaning.

You can remove the drawers to use VarioSpace.

The way to remove/insert the drawers varies depending on the pull-out system. Your appliance can contain various pull-out systems.

Note

The energy consumption increases and the cooling power goes down if ventilation is not sufficient.

- Leave the bottom drawer in the appliance!
- Always leave the fan air vents clear on the back wall!

8.7.1 Drawer on appliance base or glass shelf

The drawer runs directly on the appliance base or on a glass shelf. There are no rails.

When you remove the drawers, you can use the glass shelves below them as storage shelves.

Removing drawer




Fig. 66

• Remove drawer as shown in the illustration.

Inserting drawer




Fig. 67

▶ Insert drawer as shown in the illustration.

8.7.2 Drawer on telescopic rails

The drawer runs on extendible rails (telescopic rails). There are fully extendible telescopic rails and telescopic rails with partial pull-out. Drawers which are fully extendible can be pulled out fully from the appliance. Drawers with partial pull-out cannot be removed fully from the appliance. The system in your appliance depends on the type of appliance.

Fully extendible*

If you have fully extendible rails, there is a clamp located at the back on the left and right of the rail.

Removing drawer




Fig. 68

- Pull out drawer as far as it will go.
- ▶ Lift left clamp and simultaneously pull drawer forwards on the left. *Fig. 68 (1)*
- Lift right clamp and simultaneously pull drawer forwards on the right. Fig. 68 (2)
- Remove drawer to the front. *Fig. 68* (3)
- Slide rails in.

Inserting drawer





Fig. 69

- Slide rails in.
- Place drawer on rails.
- Slide in drawer to the back.
- \triangleright Drawer latches in audibly at the back.
- Partial pull-out fridge compartment*

Removing drawer



- Fig. 70
- ▶ Pull out drawer half-way. *Fig. 70 (1)*
- Push the drawer down at the front. Fig. 70 (2)
- Push the left rail in by about 2 cm. Fig. 70 (3)
- Push the right rail in by about 2 cm. Fig. 70 (4)
- Remove drawer to the front. Fig. 70 (5)




Fig. 71

- If the rails are not yet fully inserted after removing the drawer:
- Push rails in completely.

Inserting drawer




Fig. 72

- Slide rails in.
 Place drawer on rails.
- Slide in drawer to the back.

8.8 Fruit & Vegetable safe cover

You can remove the compartment cover for cleaning.

8.8.1 Removing the compartment cover

Ensure that the following conditions are met:

 $\hfill\square$ Bottle shelf is removed (see 8.6 Adjustable bottle shelf) .




Fig. 73

When the drawers are removed:

- Pull the lid up at the front to the opening in the retaining parts Fig. 73 (1).
- Lift from the back and pull it up and out *Fig.* 73 (2).

8.8.2 Inserting the compartment cover




Fig. 74

- If the text THIS SIDE UP points upwards:
- Insert the lip of the cover over the opening of the rear bracket Fig. 74 (1) and click into place Fig. 74 (2).
- Position the cover where you want it (see 8.9 Adjusting the moisture levels).

8.9 Adjusting the moisture levels

You can adjust the moisture in the drawer yourself by adjusting the compartment cover.

The compartment lid is attached to the drawer and can be hidden by a shelf or additional drawers.




Fig. 75

Low air humidity

- Open the drawer.
- Slide the compartment cover forwards.
- With the drawer closed: Gap between the cover and the compartment.
- \triangleright The air moisture in the Safe decreases.

High air moisture

- Open the drawer.
- ▶ Slide the cover back.
- \triangleright With the drawer closed: The cover seals the compartment.
- The air moisture in the Safe increases.
 If there is too much moisture in the compartment:
- Choose the setting "low air moisture".
 -or-
- Remove any excess moisture with a cloth.

Note

You can apply the "low air moisture" setting to the Fruit & Vegetable-Safe and the Meat & Dairy-Safe.

Set the "low air moisture" option.

8.10 Glass shelves

You can remove the glass shelves under the drawers for cleaning.

You can remove the glass shelves under the drawers to use VarioSpace.

8.10.1 Removing / inserting the glass shelf

Make sure that the following requirements are fulfilled:

□ Glass shelf under the drawer: The drawer has been removed. (see 8.7 Drawers)

Removing glass shelf





Fig. 76 Example illustration of glass shelf


- Lift glass shelf at the front. *Fig. 76 (1)*
- Take out glass shelf to the front. *Fig. 76 (2)*



- Fig. 77 Example illustration of glass shelf
- Position glass shelf at an angle behind the stoppers. (see Fig. 77)
- Lower glass shelf.
- Slide in glass shelf to the back.

8.11 EasyTwist-Ice*

With the EasyTwist-Ice you can make enough ice cubes for the whole household. The EasyTwist-Ice is supplied with water via a water tank.



- Fig. 78 Example illustration
- (1) Freezer drawer with EasyTwist-Ice
- (4) Rotary knob
- (2) Body with ice cube tray (5) Ice cube drawer
- (3) Water tank

Note

Do not change the position of the freezer drawer with the EasyTwist-Ice in the appliance.

8.11.1 Making ice cubes

The amount of ice cubes you can make in a given period of time with the EasyTwist-Ice depends on the freezer temperature of the appliance. The lower the temperature in the appliance, the more ice cubes you can make.

Maximum number of ice cubes in the ice cube tray:	20 ice cubes
Maximum capacity of the ice cube drawer:	40 ice cubes (equivalent to two ice cube batches)
More information about the time needed for ice cube production:	

Make sure that the following requirements are fulfilled: Components of the EasyTwist-Ice have been cleaned.

Filling the water tank

Risk of poisoning due to contaminated water! Only fill the water tank with potable water.

NOTICE

Sugar-content liquids! Damage to EasyTwist-Ice.

Only fill with cold drinking water.

Note

Using filtered, decarbonised water ensures the best-tasting drinking water for your ice cubes.

This water quality can be achieved using a table water filter of the kind available in trade retail outlets.

Always fill the water tank only with filtered, decarbonised drinking water.




Fig. 79

- Pull out freezer drawer as far as it will go.
- Lift the water tank at the recess Fig. 79(1).
- Remove the water tank by lifting it upwards. Fig. 79 (2)
- Fill the water tank with drinking water up to the mark *Fig. 79 (3)*.




Fig. 80

- Position the water tank at the front. Fig. 80 (1)
- Lower the water tank at the rear. *Fig. 80 (2)*
- Slide in the freezer drawer.

Releasing the ice cubes

Make sure that the following requirements are fulfilled:

- □ The required time for the production of ice cubes has been observed. (see 10.1 Technical specifications)
- Freezer drawer is fully inserted.
- Ice cube drawer is fully inserted.
- ▶ Turn the rotary knob *Fig. 78 (4)* clockwise as far as it will go.
- ▷ Ice cubes fall from the ice cube tray into the ice cube drawer *Fig. 78 (5)*.
 - If all the ice cubes do not come out of the ice cube tray:
- Turn the rotary knob clockwise several times to the stop.

8.12 VarioSpace




Fig. 81

You can remove drawers and glass panels from your appliance. This provides more room for large food items such as poultry, joints of meat, large game, and tall baked products. You can then freeze these items whole for later preparation.

Note the weight limits on the drawers and glass panels (see 10.1 Technical specifications).

8.13 Bottle holder

8.13.1 Using the bottle holder




Fig. 82

- Push the bottle holder onto the bottles.
- Dash The bottles are prevented from falling over.

8.13.2 Removing the bottle holder




Fig. 83

- Move the bottle holder all the way to the right.
- Push the bottle holder to the back to remove.

8.14 Freezer pack

Freezer packs prevent the temperature rising too quickly should there be a power cut.

The freezer packs are in the drawer.

8.14.1 Using the freezer pack




Fig. 84

When the freezer packs are fully frozen:

Place on the frozen goods in the top, front part of the freezer.

9 Maintenance

9.1 FreshAir carbon filter

The FreshAir carbon filter is in the compartment above the fan.

It guarantees the best air quality.

- □ Replace the carbon filter every 6 months.
- When the reminder is set, a message on the display prompts you to change it.
- □ The carbon filter can be disposed of with the regular household waste.

Note

FreshAir activated charcoal filters can be purchased from the Liebherr-Hausgeräte store at home.liebherr.com/shop/de/deu/zubehor.html.

9.1.1 Removing the FreshAir carbon filter




Fig. 85

- ▶ Pull out the compartment *Fig. 85 (1)*.
- Remove the carbon filter *Fig. 85 (2)*.

9.1.2 Inserting the FreshAir carbon filter




Fig. 86

- ▶ Insert the carbon filter as shown in the diagram *Fig. 86 (1).*
- > The carbon filter clicks into place.
- If the carbon filter is pointing downwards: Push the compartment in *Fig. 86 (2)*.
- The carbon filter is now ready for use.

9.2 Disassembling / assembling pullout systems

9.2.1 Notes on disassembly

You can disassemble some of the pull-out systems for cleaning. Your appliance can contain a variety of pull-out systems.

The following pull-out systems can be disassembled or cannot be disassembled:

Pull-out system	can be disassembled / cannot be disassembled
Drawer on appliance base or glass shelf	cannot be disassembled
Fully extendible*	cannot be disassembled*
Partial pull-out fridge compart- ment*	cannot be disassembled*

9.3 Defrosting the appliance

9.3.1 Defrosting the fridge compartment

Defrosting is performed automatically. The water from the thawing process drains through the outlet and evaporates.

Clean the drain opening regularly (see 9.4 Cleaning the appliance).

9.3.2 Defrosting the freezer compartment with NoFrost

Defrosting is performed automatically with the NoFrost system. The moisture is deposited on the evaporator, is periodically defrosted and evaporates.

The appliance does not need to be defrosted.

9.4 Cleaning the appliance

9.4.1 Ready

Danger of electric shock!

 Remove the refrigerator connector or interrupt the power supply.

Risk of fire

► Do not damade

- Do not damage the refrigeration circuit.
- Empty the appliance.
- Remove mains connector.
- -or-
- Activate CleaningMode.

9.4.2 Clean the housing

NOTICE

Improper cleaning!

- Damage to the appliance.
- Only use soft cleaning cloths and ph-neutral all-purpose cleaners
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

WARNING

Risk of injury and damage as a result of hot steam!

Hot steam can lead to burns and can damage the surfaces. ▶ Do not use any steam cleaners!

▶ Wipe the housing down with soft, clean cloth. If very dirty, use lukewarm water with a neutral cleaner. Glass surfaces can also be cleaned with glass cleaner.

9.4.3 Cleaning the interior

NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- ▶ Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.
- Plastic surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- Metal surfaces: clean by hand with a soft clean cloth, lukewarm water and a little detergent.
- ▶ Drain hole: remove deposits using a thin item (for example a cotton bud).

9.4.4 Clean the components

NOTICE

Improper cleaning!

Damage to the appliance.

- Only use soft cleaning cloths and ph-neutral all-purpose cleaners.
- Do not uses abrasive sponges or steel wool which may cause scratches.
- Do not use any sharp or abrasive cleaning agents, nor any that contain sand, chloride or acid.

Clean with a soft, clean cloth, lukewarm water and some detergent:

- Door rack
- Dividing shelf
- Fruit & Vegetable safe cover
- Drawer
- Adjustable bottle shelf
- Components of the EasyTwist-Ice*

Clean with a damp cloth:

Retractable rails Please note: The grease in the tracks is used for lubrication and must not be removed!

Wash in the dishwasher up to 60 °C:

- Bottle rack
- Holder of the dividing shelf
- IceMaker water tank and water tank lid

To disassemble components: see the relevant section. Clean the components.

9.4.5 Cleaning the EasyTwist-Ice


Clean the EasyTwist-Ice in the following situations:

- First use
- Not using for more than 48 hours
- When cleaning is required

Dismantling the EasyTwist-Ice

Make sure that the following requirements are fulfilled:

- □ The drawer has been removed. (see 8.7 Drawers)
- The drawer is placed on a table.





- Removing the water tank: Lift the water tank by the recess Fig. 87 (1).
- Remove the water tank Fig. 87 (2) upwards.
- Remove the ice cube drawer Fig. 87 (3) to the front. ►




Fig. 88

- ▶ Removing the EasyTwist-Ice body: Use your finger to push the tab Fig. 88 (4) down and use your other hand to lift the EasyTwist-Ice body Fig. 88 (5) from behind at the same time.
- Remove the EasyTwist-Ice body from the freezer drawer.

Shelf

VarioSafe*




Fig. 89

- ▶ Removing the EasyTwist-Ice body cover: Push the tabs *Fig. 89 (6)* on both sides of the EasyTwist-Ice body with one hand.
- ▶ Use the other hand to remove the cover Fig. 89 (7) upwards.

 \triangleright EasyTwist-Ice is dismantled into four parts. (see Fig. 90)




Fig. 90 Components of the EasyTwist-Ice

- (1) EasyTwist-Ice body (3) Cover
- with ice cube tray (2) Water tank
 - (4) Ice cube drawer

NOTICE

Risk of damage due to improper dismantling!

Equipment breaking, jumping and cracking. If you dismantle the EasyTwist-Ice body further, you may damage the rotary knob or other parts of the EasyTwist-Ice body.

- Only dismantle the EasyTwist-Ice into the components shown. (see Fig. 90)
- Clean the EasyTwist-Ice body *Fig. 90 (1)* as a whole.

Cleaning the EasyTwist-Ice

Make sure that the following requirements are fulfilled:

- □ The EasyTwist-Ice is dismantled. (see Dismantling the EasyTwist-Ice)
- Clean the ice cube drawer, water tank, cover and Easy-Twist-Ice body with warm water and a little detergent.
- Dry all cleaned components thoroughly with a dry cloth.
- ▷ The EasyTwist-Ice is clean.

Installing the EasyTwist-Ice




Fig. 91

- ▶ Installing the EasyTwist-Ice body cover: Place the cover on the front. *Fig. 91 (1)*
- Lower the cover at the rear. *Fig. 91 (2)*
- \triangleright The cover locks into both tabs *Fig. 91 (3)* audibly.




Fig. 92

- ▶ Installing the EasyTwist-Ice body: Push the axes for the EasyTwist-Ice body into the guides *Fig. 92 (4)*.
- Press the EasyTwist-Ice body *Fig. 92 (5)* down at the back.
 The EasyTwist-Ice body locks in audibly.




Fig. 93

▶ Insert the ice cube drawer Fig. 93 (6).

Risk of poisoning due to contaminated water!
 Only fill the water tank with potable water.

- ► Fill the water tank with water.
- Insert the water tank.
- Insert the drawer. (see 8.7 Drawers)
- If you are using unfiltered water:
- Dispose of ice cubes that were produced 24 hours after initial ice cube production.

-or-

If you are using filtered water:
 Dispose of ice cubes that were produced 48 hours after initial ice cube production.

9.4.6 After cleaning

- ▶ Wipe the appliance and the components dry.
- Connect and switch on the appliance.
- Activate SuperFrost (see 7.2 Appliance functions) .
- The temperature is cold enough:
- Place the food inside.

Customer help

► Repeat cleaning regularly.

10 Customer help

10.1 Technical specifications

Temperature range

. oporat	and range	
Cooling 3 °C to 9 °C		3 °C to 9 °C
BioFresh 0 °C to 3 °C		
Freeze-26 °C to -15 °C		-26 °C to -15 °C
Maximum freezing quantity/24 h		
Freezer	compart-	See "Freezing capacity/24 h" on

ment	the type plate
	See "Freezing capacity/24 h" on the type plate

Maximum component capacity

Features	Appliance width 550 mm (see instal- lation instruc- tions, appliance dimen- sions)	Appliance width 600 mm (see installa- tion instruc- tions, appliance dimen- sions)	Appliance width 700 mm (see instal- lation instruc- tions, appli- ance dimen- sions)
Drawer on glass shelf (see 8.7.1 Drawer on appliance base or glass shelf)	12 kg	15 kg	

Ice cube production with EasyTwist-Ice*			
Time required at -18 °C approx. 5.5 h			
Time required with SuperFrost activated approx			

For appliances with a WiFi connection:*

Frequency specification*		
Frequency band	2.4 GHz	
Maximum radiated power	< 100 mW	
	Integration in the local WiFi network for data communication	

10.2 Operating noises

The appliance makes different noises when it is on.

- At higher temperatures the appliance uses less energy but works for longer. It is quieter.
- At lower temperatures the food is cooled faster. It is louder.

Examples:

- Functions on (see 7.2 Appliance functions)
- Fan running
- Food recently added
- High ambient temperature
- Door open for a while

Noise		Possible cause		Type of noise		
Bubbling and splashing		Coolant into the circuit.				operating
Hissing		Coolant into the circuit.	sprays cooling			operating
Humming		The appliance is cooling. The volume depends on the cooling output.				operating
Suction noises		Soft-closi is being and close	opened	-		operating
Humming and rustling		The fan is	running.	Norr nois		operating
Clicking		Componer switched off.				switching
Rattling or humming		Valves or working.	flaps are	Norr nois		switching
		sible	Type of no	oise	Lift	ing

Noise	Possible cause	Type of noise	Lifting
Vibration	Improper setup	Defective noise	Level the appliance using the adjustable feet.
Rattling	Components, items inside	Defective noise	Secure components.
	the appliance		Leave enough space between the items.

10.3 Technical fault

Your appliance is designed and built to ensure it works reliably and has a long service life. In the unlikely event that a fault occurs during operation, please check whether it is due to an operating error. If so, you will be charged for the callout and repair costs even if it falls within the warranty period.

You can fix the following faults yourself.

10.3.1 Appliance function

Defect	Cause	Remedy
The appliance is not working.	\rightarrow The appliance is not switched on.	 Switch the appliance on.

Defect	Cause	Remedy
	→ The power plug is not properly plugged into the socket.	 Check the power plug.
	→ There is something wrong with the power outlet fuse.	 Check the fuse.
	→ Power cut	 Keep the appliance closed. Protecting food: Lay freezer packs on top of the food or use another freezer if the power is off for a prolonged period. Do not re-freeze defrosted food,
	→ The appliance plug does not fit the appliance properly.	 Check the appliance plug.
Temperature is not cold enough.	→ The appliance door is not closed properly.	 Close the appliance door.
	\rightarrow Not enough ventilation.	 Keep ventilation grille clear, and clean it.
	→ The ambient temperature is too high.	 Solution: (see 1.4 Appliance range of use).
	→ The appliance was opened too many times or for too long.	 Wait to see if the required temperature corrects itself. If not, contact Customer Service. (see 10.4 Customer Service)
	→ Too much fresh food was placed inside without SuperFrost.	 Solution: (see SuperFrost)
	ightarrow The temperature is set incorrectly.	► Turn down the temperature and check after 24 hours.
	→ The appliance is too close to a heat source (oven, radiator, etc).	Move the appliance or the heat source.
The door seal is defective or needs to be replaced for another reason.	→ You can replace the door seal, depending on your model. It can be replaced without the need for special tools.	 Contact Customer Service. (see 10.4 Customer Service)
The door seal is defective or needs to be replaced for another reason.	→ The door seal can be replaced. It can be replaced without the need for special tools.	 Contact Customer Service. (see 10.4 Customer Service)
The appliance builds up too much ice or condensa- tion.	→ The door seal may have slipped out of its groove.	 Check that the door seal is well fitted in the groove.
The appliance is hot to touch on the outside*.	→ The heat of the refrigeration circuit is used to avoid condensation.	This is normal.

10.3.2 Features

Defect	Cause	Remedy		
The internal light	\rightarrow The appliance is not switched on.	 Switch the appliance on. 		
does not come on.	→ The door was open for longer than 15 minutes.	 Interior lighting turns off automatically after approx. 15 min. with the door open. 		
	→ The LED interior light is faulty or the lid is damaged.	 Contact Customer Service. (see 10.4 Customer Service) 		
The freezer compartment cannot be closed.	→ The lock is on when the door is open.	 Use the handle again. 		

10.4 Customer Service

First check whether you can rectify the fault yourself (see 10 Customer help) . If you cannot rectify the problem, contact Customer Service.

You can find the address in the enclosed brochure "Liebherr-Service" or at home.liebherr.com/service.



Unprofessional repair! Injuries.

- Have any repairs and action not expressly specified on the appliance and mains cable carried out by service personnel only. (see 9 Maintenance)
- A damaged mains cable may only be replaced by the manufacturer, the manufacturer's Customer Service or a similarly qualified person.
- ► In the case of appliances with an IEC connector, the change may be made by the customer.

10.4.1 Contacting Customer Service

Make sure that the following appliance information is available:

□ Appliance name (model and index)

- Service no. (Service)
- □ Serial no. (S no.)
- Call up the appliance information via the display. (see Info)
- -or-
- Refer to the type plate for appliance information. (see 10.5 Model plate)
- ▶ Note down the appliance information.
- Notify customer service: Report errors and the appliance information.
- \triangleright This will help us to provide you with a faster, more accurate service.
- ► Follow further instructions from Customer Service.

10.5 Model plate

The model plate is behind the drawers on the inside of the appliance.




Fig. 94

(1) Appliance description
 (3) Serial no.
 (2) Service no.

▶ Note the data on the model plate.

11 Shutting down

- Empty the appliance.
- Switch off appliance. (see Turn off appliance)
- Remove mains connector.
- Remove appliance connector if required: Remove and move from left to right at the same time.
- Clean appliance. (see 9.4 Cleaning the appliance)
- ► Leave the door open to avoid bad smells building up.

12 Disposal

12.1 Preparing appliance for disposal



Liebherr uses batteries in some of its appliances. In the EU, for environmental reasons, legislation obliges the end user to remove these batteries before disposing of old appliances. If your appliance contains batteries, a corresponding notice is attached.

Lamps If you can remove the lamps yourself without destroying them, also remove these before disposal.

- ► Take the appliance out of operation.
- Appliances with batteries: remove the batteries. For description, see Maintenance chapter.
- ▶ If possible: remove lamps without destroying them.

12.2 Disposing of the appliance in an environmentally friendly manner



The appliance still contains valuable materials and must be disposed of separately from unsorted municipal waste.



Dispose of batteries separately from the old appliance. To do this, you can return the batteries free of charge to retailers as well as recycling centres and collection centres for recyclable materials.

of removed

lamps

Lamps

For Germany:

via the respective collection systems. You can dispose of the appliance free of charge via the class 1 collection containers at the local recycling and recyclable material collection centres. When purchasing a new fridge/freezer, if the sales area > 400 m², retailers will also take

back the old appliance free of



Leaking coolant and oil!

Fire. The coolant contained in the appliance is eco-friendly, but also flammable. The oil contained in the appliance is flammable. Escaping coolant and oil can ignite if the concentration is high enough and in contact with an external heat source.

charge.

Dispose

- ► Do not damage the pipelines of the coolant circuit and the compressor.
- ▶ Transport the appliance without damaging it.
- Dispose of batteries, lamps and the appliance according to the above specifications.



home.liebherr.com/fridge-manuals

EN fridge/freezer with BioFresh

Issue date: 20231214

Part number index: 7083576-00

Liebherr-Hausgeräte Marica EOOD Bezirk Plovdiv 4202 Radinovo Bulgarien