



Seagate® Nytro® 1351, 1551 SSD

Product Manual

Nytro 1351 - Read Intensive Models

Nytro 1551 - Mixed Workload Models

SED - TCG Enterprise

XA240LE10023
XA480LE10083
XA960LE10083
XA1920LE10083
XA3840LE10083

SED - TCG Opal

XA240LE10043
XA480LE10103
XA960LE10103
XA1920LE10103
XA3840LE10103

Standard

XA240LE10003
XA480LE10063
XA960LE10063
XA1920LE10063
XA3840LE10063

SED - TCG Enterprise

XA240ME10023
XA480ME10083
XA960ME10083
XA1920ME10083
XA3840ME10083

SED - TCG Opal

XA240ME10043
XA480ME10103
XA960ME10103
XA1920ME10103
XA3840ME10103

Standard

XA240ME10003
XA480ME10063
XA960ME10063
XA1920ME10063
XA3840ME10063

Revision History

| Version and Date | Description of Changes |
|------------------|--------------------------------|
| Rev A, July 2018 | First release of the document. |

© 2018, Seagate Technology LLC All rights reserved. Publication number: 100834145, Rev A, July 2018

Seagate Technology reserves the right to make changes to the product(s) or information disclosed herein at any time without notice.

Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Nitro and DuraWrite are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners.

No part of this publication may be reproduced in any form without written permission of Seagate Technology LLC. Call 877-PUB-TEK1(877-782-8351) to request permission.

When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual quantities will vary based on various factors, including file size, file format, features and application software. Actual data rates may vary depending on operating environment and other factors. The export or re-export of hardware or software containing encryption may be regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and controlled for import and use outside of the U.S. Seagate reserves the right to change, without notice, product offerings or specifications.

Contents

| | |
|------------------------------------------------------------|-----------|
| Seagate Technology Support Services | 5 |
| 1. Introduction | 6 |
| 2. Specifications | 9 |
| 2.1 Models and Capacity | 9 |
| 2.2 Performance | 10 |
| 2.3 Power | 12 |
| 2.4 Environmental Conditions | 13 |
| 2.5 Reliability | 14 |
| 2.6 Tunable Capacity | 14 |
| 2.7 Endurance | 15 |
| 3. Mechanical Information | 16 |
| 3.1 Dimensions and Weight | 16 |
| 4. Pin and Signal Descriptions | 17 |
| 4.1 Serial ATA Interface Connector | 17 |
| 4.2 Pin Locations | 18 |
| 4.3 Connector Pin Signal Definitions | 18 |
| 4.4 Power Pin Signal Definitions | 19 |
| 4.5 SSD Activity LED Indicator (Optional) | 19 |
| 5. Supported ATA Command List | 21 |
| 5.1 ATA Feature Set | 21 |
| 5.2 ATA Command Description | 22 |
| 5.3 Security | 23 |
| 5.3.1 Password Loss | 23 |
| 6. SMART Support | 24 |
| 6.1 SMART Command Set | 24 |
| 6.2 SMART Attributes | 25 |
| 6.3 SMART Trip | 26 |
| 7. Standards and Reference Documents | 27 |
| 7.1 Regulatory Model Numbers | 27 |
| 7.2 Agency and Safety Certifications | 27 |
| 7.2.1 Safety Certification | 27 |
| 7.2.2 Electromagnetic Compatibility | 27 |
| 7.2.3 Electromagnetic Susceptibility | 27 |
| 7.2.4 Electromagnetic Compliance | 27 |
| 7.2.5 European Union (EU) CE Marking Requirements | 28 |
| 7.2.6 Australian and New Zealand RCM Compliance Mark | 28 |
| 7.2.7 Canada ICES-003 | 28 |
| 7.2.8 South Korean Certification Mark | 28 |
| 7.2.9 Morocco Commodity Mark | 28 |
| 7.2.10 Taiwanese BSMI | 29 |
| 7.3 Environmental Protection | 29 |

| | |
|-------------------------------------------------------------------|----|
| 7.3.1 European Union Restriction of Hazardous Substance Law | 29 |
| 7.3.2 China Requirements —China RoHS 2 | 30 |
| 7.3.3 Taiwan Requirements — Taiwan RoHS | 31 |

Seagate Technology Support Services

For Nytro® Support, visit: <http://www.seagate.com/support/by-product/ssd-and-pcie-flash/>

For information regarding online support and services, visit: <http://www.seagate.com/contacts/>

Available services include:

- Presales & Technical support
- Global Support Services telephone numbers & business hours
- Authorized Service Centers

For information regarding Warranty Support, visit: <http://www.seagate.com/support/warranty-and-replacements/>

1. Introduction

The Seagate® Nytro® 1351 and Nytro 1551 are next generation enterprise SATA SSDs that deliver enterprise class features in a 2.5-inch × 7 mm form factor.

Table 1 Features

| Feature | Description |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Capacity | <ul style="list-style-type: none"> ■ 240, 480, 960, 1920, or 3840 GB |
| Certifications, Eco-Compliance | <ul style="list-style-type: none"> ■ CE, UL, cUL, RCM, BSMI, KCC, TUV, Microsoft WHCK, Microsoft WHQL, SATA-IO ■ RoHS, WEEE |
| Dimension | <ul style="list-style-type: none"> ■ Width: 69.85±0.25 millimeters ■ Length: 100±0.25 millimeters ■ Height: Maximum 7 millimeters |
| Endurance | <ul style="list-style-type: none"> ■ Lifetime Endurance: 1 or 3 DWPD depending on the model |
| Logical Block Size | <ul style="list-style-type: none"> ■ 512 bytes |
| Form Factor | <ul style="list-style-type: none"> ■ 2.5 inch × 7 mm Standard SSD |
| Interface Compliance | <ul style="list-style-type: none"> ■ Fully compliant with SATA revision 3.2 and 3.3, compatible with SATA 6.0Gb/s and 3.0Gb/s interface rates. ■ Fully compliant with ATA/ATAPI Command Set – 4 and supports all mandatory ATA commands defined in the ATA8-ACS specification. <ul style="list-style-type: none"> — ATA General Feature Command Set — Power Management Command Set — Security Mode Feature Set — SMART Command Set — Device Statistics — SMART Command Transport — Dataset Management Command Set — Host Protected Area Command Set — 48-bit Address Command Set — General Purpose Log Command Set — Native Command Queuing — Software Settings Prevention — ATA Sanitize Command Set — Identify Device Command Set — Log Addresses Requirement ■ PIO, DMA, UDMA (up to 6, dependent on host) supported. ■ SATA 6.0Gb/s Native Command Queuing (NCQ): up to 32 commands. ■ SMART command transport (SCT) technology. ■ Data Set Management Command Trim support. |
| NAND | <ul style="list-style-type: none"> ■ 3D eTLC |
| Flash Controller | <ul style="list-style-type: none"> ■ Seagate proprietary Flash Controller ■ Seagate DuraWrite™ Technology for improved performance |
| Performance | <ul style="list-style-type: none"> ■ See Section 2.2, Performance, on page 10. |
| Power Consumption | <ul style="list-style-type: none"> ■ See Section 2.3, Power, on page 12. |

Table 1 Features (Continued)

| Feature | Description |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Loss Data Protection | <ul style="list-style-type: none"> ■ In-process writes to the NAND are completed in the event of an unexpected power loss |
| Power Management | <ul style="list-style-type: none"> ■ OS-aware hot-plug/hot-swap support |
| Power On Ready | <ul style="list-style-type: none"> ■ See Section 2.3, Power, on page 12. |
| Reliability | <ul style="list-style-type: none"> ■ Power-loss data protection ■ SMART thermal monitoring ■ MTBF: 2 million hours @ 55 C ■ UBER: 1 read error per 10¹⁷bits read ■ End-to-End data-path protection ■ Seagate SHIELD – Advanced ECC for improved reliability with minimal impact on performance <ul style="list-style-type: none"> — Adaptive Code Rates — Intelligent Noise handling — Adaptive Read Voltage calibration — Multi-Level Error Correction - Best-in-class LDPC implementation ■ Seagate RAISE (Redundant Array of Independent Silicon Elements) <ul style="list-style-type: none"> — Protects user data from various flash silicon failures — RAID-like data protection and recovery from flash memory failures — Operates within a single drive without impacting performance — Corrects a single page, single block or single die failure within one RAISE stripe on capacities 480GB and higher. For 240GB, corrects a single page, single block or single plane failure within one RAISE stripe. |
| Security | <ul style="list-style-type: none"> ■ Seagate Secure™ ■ Secure Supply Chain <ul style="list-style-type: none"> — O-TTPS (Open Trusted Technology Provider Standard) compliant ■ SD&D (Secure Download & Diagnostics) <ul style="list-style-type: none"> — Cryptographic FW signing, RSA 2048 key — Secure Boot — Locked Diagnostic Port — FW Authenticity and Integrity Verification, SHA 256 ■ Instant Secure Erase ■ TCG Enterprise Protocol, AES-256 Encryption models ■ TCG Opal Protocol, AES-256 Encryption models |
| Shock | <ul style="list-style-type: none"> ■ Operating: 1000G, duration 0.5ms ■ Non-Operating: 1000G, duration 0.5ms |
| Vibration | <ul style="list-style-type: none"> ■ Operating: Random, 3.8 Grms, 10-3000Hz, Uniform PSD:0.005 G²/Hz ■ Non-Operating: Random, 7 Grms, 10-500Hz, Uniform PSD:0.01 G²/Hz |
| Voltage | <ul style="list-style-type: none"> ■ 5 V (240GB, 480GB) ■ 5 V and 12 V (960GB, 1920GB, 3840GB) |
| Data Retention | <ul style="list-style-type: none"> ■ 3 months power-off retention at 40 C once the drive reaches the rated write endurance (EOL) |
| Temperature Range | <ul style="list-style-type: none"> ■ Operating: 0°C to 70°C ■ Non-operating: -40°C to 85°C |
| Thermal gradient | <ul style="list-style-type: none"> ■ Operating: 20°C/hour ■ Non-operating: 30°C/hour |

Table 1 Features (Continued)

| Feature | Description |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tunable Capacity | ■ Set to Capacity Optimized or Performance Optimized |
| TBW | ■ Up to 21000 TBW. |
| Warranty | ■ Five years limited Warranty with Media Usage, based on the shorter of term or endurance usage of the drive. See Section 2.7, Endurance, on page 15 . |
| Weight | ■ up to 77g \pm 5% |

2. Specifications

2.1 Models and Capacity

Table 2 Nytro 1351 - Read Intensive - 1 DWPD Models

| Capacity (GB) | LBA Count | SED - TCG Enterprise | SED - TCG Opal | Standard |
|---------------|----------------|----------------------|----------------|---------------|
| 240 | 46,88,62,128 | XA240LE10023 | XA240LE10043 | XA240LE10003 |
| 480 | 93,77,03,088 | XA480LE10083 | XA480LE10103 | XA480LE10063 |
| 960 | 1,87,53,85,008 | XA960LE10083 | XA960LE10103 | XA960LE10063 |
| 1920 | 3,75,07,48,848 | XA1920LE10083 | XA1920LE10103 | XA1920LE10063 |
| 3840 | 7,50,14,76,528 | XA3840LE10083 | XA3840LE10103 | XA3840LE10063 |

Table 3 Nytro1551 - Mixed Workload - 3 DWPD Models

| Capacity (GB) | LBA Count | SED - TCG Enterprise | SED - TCG Opal | Standard |
|---------------|----------------|----------------------|----------------|---------------|
| 240 | 46,88,62,128 | XA240ME10023 | XA240ME10043 | XA240ME10003 |
| 480 | 93,77,03,088 | XA480ME10083 | XA480ME10103 | XA480ME10063 |
| 960 | 1,87,53,85,008 | XA960ME10083 | XA960ME10103 | XA960ME10063 |
| 1920 | 3,75,07,48,848 | XA1920ME10083 | XA1920ME10103 | XA1920ME10063 |
| 3840 | 7,50,14,76,528 | XA3840ME10083 | XA3840ME10103 | XA3840ME10063 |

2.2 Performance

Table 4 Performance - Capacity Optimized (7% OP)

| Capacity | Units | 240 GB | | 480 GB | | 960 GB | | 1920 GB | | 3840 GB | |
|------------------------|-------|--------|------|--------|------|--------|------|---------|------|---------|------|
| | | 0% | 20% | 0% | 20% | 0% | 20% | 0% | 20% | 0% | 20% |
| 128K SR QD32 | MB/s | 560 | 560 | 560 | 560 | 560 | 560 | 560 | 560 | 560 | 560 |
| 128K SW QD32 | MB/s | 240 | 345 | 465 | 535 | 535 | 535 | 535 | 535 | 535 | 535 |
| 4K RR QD32 | KIOPs | 55 | 55 | 75 | 75 | 90 | 90 | 90 | 90 | 85 | 85 |
| 4K R70R QD32 | KIOPs | 20 | 30 | 25 | 40 | 35 | 50 | 45 | 65 | 45 | 60 |
| 4K RW QD32 | KIOPs | 12 | 30 | 15 | 50 | 20 | 55 | 20 | 50 | 20 | 45 |
| 8K RR QD32 | KIOPs | 45 | 45 | 55 | 55 | 55 | 55 | 55 | 55 | 55 | 55 |
| 8K R70R QD32 | KIOPs | 12 | 25 | 15 | 30 | 20 | 35 | 30 | 45 | 30 | 45 |
| 8K RW QD32 | KIOPs | 6 | 20 | 8 | 30 | 13 | 40 | 14 | 40 | 12 | 40 |
| 4K RR Latency QD1 | usec | 155 | 155 | 155 | 155 | 155 | 155 | 160 | 160 | 175 | 175 |
| 4K RW Latency QD1 | usec | 80 | 40 | 65 | 40 | 60 | 40 | 60 | 35 | 60 | 40 |
| 4K RR QD32 99% CI | usec | 1700 | 1580 | 760 | 720 | 580 | 600 | 570 | 560 | 730 | 700 |
| 4K R70R QD32 99% CI | usec | 6160 | 4500 | 4980 | 3620 | 3900 | 3020 | 3650 | 2710 | 3470 | 2610 |
| 4K RW QD32 99% CI | usec | 4980 | 2920 | 3720 | 1630 | 2940 | 800 | 2880 | 1830 | 2950 | 1960 |
| 4K RR QD32 99.99% CI | usec | 2000 | 2000 | 1720 | 1440 | 800 | 950 | 850 | 860 | 1850 | 1780 |
| 4K R70R QD32 99.99% CI | usec | 12450 | 8620 | 9420 | 7450 | 7770 | 6330 | 6710 | 5290 | 5970 | 5550 |
| 4K RW QD32 99.99% CI | usec | 7440 | 5580 | 5740 | 2990 | 4360 | 2090 | 3650 | 2000 | 3830 | 2110 |

NOTE

Information on performance:

- MB is 10^6 . MB/s = 10^6 bytes/sec.
- 4 KB = 4,096 bytes, 8 KB = 8,192 bytes.
- All workloads set to 4 KB alignment.
- Data compressibility values of 0% and 20% as set with VDBench.
- All metrics represent sustained values, across full LBA range.
- Performance measured with queue depth set to 32.
- Drive write cache enabled. Due to the PLDP feature, the SSD always behaves as if WCE is enabled.
- Performance test precondition: Drive is preconditioned with 2x drive capacity 128 KB write IOs.
- Results obtained with a direct SATA port connection to host. Results may vary with system configuration.

Table 5 Performance - Performance Optimized (28% OP)

| Capacity | Units | 200 GB | | 400 GB | | 800 GB | | 1600 GB | | 3200 GB | |
|------------------------|-------|--------|------|--------|------|--------|------|---------|------|---------|------|
| | | 0% | 20% | 0% | 20% | 0% | 20% | 0% | 20% | 0% | 20% |
| 128K SR QD32 | MB/s | 560 | 560 | 560 | 560 | 560 | 560 | 560 | 560 | 560 | 560 |
| 128K SW QD32 | MB/s | 240 | 345 | 465 | 535 | 535 | 535 | 535 | 535 | 535 | 535 |
| 4K RR QD32 | KIOPs | 55 | 55 | 80 | 80 | 90 | 90 | 90 | 90 | 90 | 90 |
| 4K R70R QD32 | KIOPs | 25 | 30 | 35 | 45 | 45 | 55 | 55 | 70 | 55 | 70 |
| 4K RW QD32 | KIOPs | 20 | 30 | 30 | 65 | 45 | 65 | 45 | 65 | 35 | 60 |
| 8K RR QD32 | KIOPs | 45 | 45 | 55 | 55 | 55 | 55 | 55 | 55 | 55 | 55 |
| 8K R70R QD32 | KIOPs | 20 | 25 | 25 | 35 | 35 | 40 | 40 | 45 | 35 | 45 |
| 8K RW QD32 | KIOPs | 12 | 20 | 15 | 40 | 30 | 45 | 30 | 45 | 20 | 35 |
| 4K RR Latency QD1 | usec | 155 | 155 | 155 | 150 | 145 | 140 | 145 | 140 | 155 | 150 |
| 4K RW Latency QD1 | usec | 45 | 40 | 45 | 40 | 45 | 40 | 45 | 40 | 55 | 40 |
| 4K RR QD32 99% CI | usec | 1490 | 1580 | 690 | 670 | 500 | 550 | 500 | 500 | 610 | 580 |
| 4K R70R QD32 99% CI | usec | 4900 | 4500 | 3950 | 3480 | 3500 | 2860 | 2970 | 2420 | 3060 | 2140 |
| 4K RW QD32 99% CI | usec | 3870 | 2920 | 2970 | 1590 | 1560 | 700 | 1130 | 690 | 1970 | 810 |
| 4K RR QD32 99.99% CI | usec | 2000 | 2000 | 1210 | - | - | 870 | 800 | 790 | 1030 | 980 |
| 4K R70R QD32 99.99% CI | usec | 9140 | 8620 | 8280 | 7640 | 6800 | 5700 | 5750 | 4990 | 5840 | 4950 |
| 4K RW QD32 99.99% CI | usec | 5990 | 5580 | 5580 | - | 3330 | 1810 | 2670 | 1500 | 2870 | 2000 |

NOTE

Information on performance:

- MB is 10⁶. MB/s = 10⁶ bytes/sec.
- 4 KB = 4,096 bytes, 8 KB = 8,192 bytes.
- All workloads set to 4 KB alignment.
- Data compressibility values of 0% and 20% as set with VDBench.
- All metrics represent sustained values, across full LBA range.
- Performance measured with queue depth set to 32.
- Drive write cache enabled. Due to the PLDP feature, the SSD always behaves as if WCE is enabled.
- Performance test precondition: Drive is preconditioned with 2x drive capacity 128 KB write IOs.
- Results obtained with a direct SATA port connection to host. Results may vary with system configuration.

2.3 Power

The drive uses either 5 V or it uses 5 and 12 V DC power.

Table 6 Power

| | 240 GB | 480 GB | 960 GB | 1920 GB | 3840 GB |
|---------------------------------------------------------------|--------|--------|--------|---------|---------|
| Power | | | | | |
| Voltage (V) | 5 | 5 | 5 / 12 | 5 / 12 | 5 / 12 |
| Power Consumption | | | | | |
| Overall average active power (W) | 2.3 | 2.7 | 3.2 | 3.4 | 3.5 |
| Maximum average active power (W) | 2.6 | 3.2 | 4.5 | 5.1 | 5.0 |
| Peak (25uS sample) burst active power (W) 5V limited to 6W | 4.9 | 5.4 | 7.8 | 8.8 | 8.6 |
| Idle (W) | 1.1 | 1.1 | 1.2 | 1.2 | 1.2 |

NOTE 5V power limited to 6 W beyond which power will be drawn from 12 V.

2.4 Environmental Conditions

Table 7 Temperature, Humidity, Shock

| Specification | Values |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| Temperature | <ul style="list-style-type: none"> ■ Operating: 0°C to 70°C ■ Non-operating: -40°C to 85°C |
| Humidity | <ul style="list-style-type: none"> ■ Operating and Non-Operating: 5% - 95% |
| Shock | <ul style="list-style-type: none"> ■ Operating: 1000G, duration 0.5ms ■ Non-Operating: 1000G, duration 0.5ms |
| Thermal gradient | <ul style="list-style-type: none"> ■ Operating: 20°C/hour ■ Non-operating: 30°C/hour |

NOTE

Operating, as measured by temperature sensor, SMART Attribute ID 194.

- Measured without condensation.
- The Shock specification assumes that the SSD is mounted securely with the input vibration applied to the drive mounting. Stimulus may be applied in the X, Y or Z axis.
- Operating Shock: The drive, as installed for normal operation, operates error-free while subjected to intermittent shock not exceeding specification. Shock may be applied in the X, Y, or Z-axis. Shock must not be repeated more than once every 2 seconds.
- Non-Operating Shock: The limits of non-operating shock applies to all conditions of handling and transportation. This includes isolated and integrated drives. Shock may be applied in the X, Y, or Z-axis.

Table 8 Vibration

| Specification | Values |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum Vibrations | <ul style="list-style-type: none"> ■ Operating: Random, 3.8 Grms, 10-3000Hz, Uniform PSD:0.005 G²/Hz ■ Non-Operating: Random, 7 Grms, 10-500Hz, Uniform PSD:0.01 G²/Hz |

NOTE

The Vibration specification assumes that the SSD is mounted securely with the input Vibration applied to the drive mounting screws. Stimulus may be applied in the X, Y or Z axis.

- Operating Vibration: The drive, as installed for normal operation, shall operate error free while subjected to specified vibration not exceeding specification. Vibration may be applied in the X, Y, or Z-axis.
- Non-Operating Vibration: The limits of non-operating vibration shall apply to all conditions of handling and transportation. This includes both isolated drive and integrated drives. Vibration may be applied in the X, Y, or Z-axis.

2.5 Reliability

Table 9 Reliability

| Specification | Values |
|-----------------------------------|----------------------------------------|
| Mean time between failures (MTBF) | 2 million hours @ 55°C |
| Uncorrectable Bit Error Rate | <1 error in 10 ¹⁷ bits read |

NOTE The SSD achieves the specified MTBF in an operational environment that complies with the operational temperature range specified in this manual. Operating temperatures are measured by the temperature sensor, SMART Attribute ID, Primary Temperature, provided in Table 16, "SMART Attributes," on page 25.

2.6 Tunable Capacity

You can set the SSD to Capacity Optimized or Performance Optimized states. When shipped, the SSD is in the Capacity Optimized state. Use the Seagate utility, SeaTools™ SSD to set the states. Seagate recommends to set the required state at deployment, prior to installing a file system. Changing states does not change the rated TWB specification for endurance.

2.7 Endurance

Table 10 Total Bytes Written

| Specification | 240 GB | 480 GB | 960 GB | 1920 GB | 3840 GB |
|---------------|---------|---------|---------|----------|----------|
| Nytro 1351 | 435 TB | 875 TB | 1750 TB | 3500 TB | 7000 TB |
| Nytro 1551 | 1300 TB | 2600 TB | 5250 TB | 10500 TB | 21000 TB |

NOTE

Information on endurance:

- TB=10¹² bytes
- DWPD is drive write per day.
- Limited Warranty with Media Usage provides coverage for the warranty period or the endurance usage of the drive, which ever comes first.
- Nytro 1551 endurance rating assumes that a typical enterprise data workload has 80% entropy. The SSD is fully warranted for enterprise workloads regardless of data entropy.
- SSD endurance is based on lifetime writes to the SSD from the host.
- Lifetime writes from host are available from the corresponding SMART attribute, see [Table 16, SMART Attributes, on page 25](#).

3. Mechanical Information

3.1 Dimensions and Weight

Weight: 77 g


Height: Maximum 7 mm

Width: 69.85±0.25

Length: 100±0.25

NOTE All dimensions are in millimeters.


Figure 1 Dimensions



4. Pin and Signal Descriptions


4.1 Serial ATA Interface Connector

Figure 2 Connector Physical Dimension and Connector Assembly



4.2 Pin Locations

Figure 3 Layout of 2.5-inch Signal and Power Segment Pins



NOTE The 2.5-inch connector supports built in latching capability.

4.3 Connector Pin Signal Definitions

Table 11 Serial ATA Connector Pin Signal Definitions—2.5-inch Form Factors

| Pin | Name | Definition |
|-----|--------|------------------------------------|
| S1 | Ground | Ground |
| S2 | A+ | Differential signal pair +A and A- |
| S3 | A- | |
| S4 | Ground | Ground |
| S5 | B- | Differential signal pair +B and B- |
| S6 | B+ | |
| S7 | Ground | Ground |

NOTE Key and spacing separate the signal and power segments.

4.4 Power Pin Signal Definitions

Table 12 Serial ATA Power Pin Signal Definitions—2.5-inch Form Factors

| Pin | Function | Definition |
|-----|----------|------------------------------|
| P1 | V33 | 3.3 V Power; not used |
| P2 | V33 | 3.3 V Power; not used |
| P3 | V33 | DevSlp; do not connect 3.3 V |
| P4 | GND | Ground |
| P5 | GND | Ground |
| P6 | GND | Ground |
| P7 | V5 | 5 V Power |
| P8 | V5 | 5 V Power |
| P9 | V5 | 5 V Power |
| P10 | GND | Ground |
| P11 | DAS | Device Activity Signal |
| P12 | GND | Ground |
| P13 | V12 | 12 V Power |
| P14 | V12 | 12 V Power |
| P15 | V12 | 12 V Power |

NOTE

Key and spacing separate the signal and power segments.

- Uses 12 V and 5 V power only. The 240 GB and 480 GB models use 5 V supply only.
- Ground pins are P4, P5, P6, P10, and P12.
- P7, P8, and P9 are 5V power pins and are connected internally on the drive.
- P13, P14, and P15 are 12V power pins and are connected internally on the drive.

4.5 SSD Activity LED Indicator (Optional)

The SSD can support DAS Control function from the SSD module to indicate LED activity of host side.


The device includes a physical pin P11 for connecting device activity LEDs.

The signal provided to indicate activity of the device is a low-voltage and low-current driver. The signal from the device is not suitable for directly driving an LED and is first buffered using a circuit external to the device before driving an LED.

The DAS function firmware feature generates a Low and High toggle Activity signal on pin 11 when the SSD is in a busy state and generates a high Activity signal input when the SSD is in idle mode (Low level: GND, High level: 2.85 V).

The DAS Firmware feature is disabled and the R das is opened when the DAS function is not in use. See [Figure 4, Circuit of SSD Activity LED indication, on page 20](#).

Figure 4 Circuit of SSD Activity LED indication



5. Supported ATA Command List

The SSD complies with ATA-8/ACS-4. All mandatory and many optional commands and features are supported.

5.1 ATA Feature Set

The following table shows the ATA feature set and commands that the SSD supports.

Table 13 ATA Feature Set

| Feature |
|---------------------------------|
| Power Management Command Set |
| Security Mode Feature Set |
| SMART Command Set |
| Device Statistics |
| SMART Command Transport |
| Dataset Management Command Set |
| Host Protected Area Command Set |
| 48-bit Address Command Set |
| General Purpose Log Command Set |
| Native Command Queuing |
| Software Settings Prevention |
| ATA Sanitize Command Set |
| Identify Device Command Set |

5.2 ATA Command Description

The following table shows the ATA commands supported.

Table 14 ATA Command Description

| Command | Code (Hex) | Command | Code (Hex) |
|-------------------------------|------------|----------------------------|------------|
| NOP | 00h | EXECUTE DEVICE DIAGNOSTICS | 90h |
| DATA SET MANAGEMENT | 06h | DOWNLOAD MICROCODE | 92h |
| REQUEST SENSE DATA EXT | 08h | DOWNLOAD MICROCODE DMA | 93h |
| READ SECTORS | 20h | SMART | B0h |
| READ SECTORS EXT | 24h | SANITIZE DEVICE | B4h |
| READ DMA EXT | 25h | READ MULTIPLE | C4h |
| READ MULTIPLE EXT | 29h | WRITE MULTIPLE | C5h |
| READ LOG EXT | 2Fh | SET MULTIPLE MODE | C6h |
| WRITE SECTORS | 30h | READ DMA | C8h |
| WRITE SECTORS EXT | 34h | WRITE DMA | CAh |
| WRITE DMA EXT | 35h | WRITE MULTIPLE FUA EXT | CEh |
| WRITE MULTIPLE EXT | 39h | STANDBY IMMEDIATE | E0h |
| WRITE DMA FUA EXT | 3Dh | IDLE IMMEDIATE | E1h |
| WRITE LOG EXT | 3Fh | STANDBY | E2h |
| READ VERIFY SECTORS | 40h | IDLE | E3h |
| READ VERIFY SECTORS EXT | 42h | READ BUFFER | E4h |
| ZERO EXT | 44h | CHECK POWER MODE | E5h |
| WRITE UNCORRECTABLE EXT | 45h | SLEEP | E6h |
| READ LOG DMA EXT | 47h | FLUSH CACHE | E7h |
| WRITE LOG DMA EXT | 57h | WRITE BUFFER | E8h |
| TRUSTED NON-DATA | 58h | READ BUFFER DMA | E9h |
| TRUSTED RECEIVE | 5Ch | FLUSH CACHE EXT | EAh |
| TRUSTED RECEIVE DMA | 5Dh | WRITE BUFFER DMA | EBh |
| TRUSTED SEND | 5Eh | IDENTIFY DEVICE | ECh |
| TRUSTED SEND DMA | 5Fh | SET FEATURES | EFh |
| READ FPDMA QUEUED | 60h | SECURITY SET PASSWORD | F1h |
| WRITE FPDMA QUEUED | 61h | SECURITY UNLOCK | F2h |
| NCQ QUEUE MANAGEMENT | 63h | SECURITY ERASE PREPARE | F3h |
| SEND FPDMA QUEUED | 64h | SECURITY ERASE UNIT | F4h |
| RECEIVE FPDMA QUEUED | 65h | SECURITY FREEZE LOCK | F5h |
| SET DATE & TIME EXT | 77h | SECURITY DISABLE PASSWORD | F6h |
| ACCESSIBLE MAX ADDRESS CONFIG | 78h | | |

5.3 Security

The user/master password is supported.

When the device receives a normal SECURITY ERASE UNIT command, the device erases all data blocks including unallocated (hidden) blocks.

You can download firmware regardless of the security state.

Other security features:

- TCG- Enterprise and TCG-Opal support
- Crypto-erase sanitization
- Block-level sanitization
- Secure update of firmware

5.3.1 Password Loss

If you lose the user password, you can access the device using the master password. If both passwords are lost, there is no way to access the device. For TCG Opal SSDs, where the credentials are no longer known, PSID Revert can be used to regain the use of the SSD but all of the data on the drive will be erased.

6. SMART Support

6.1 SMART Command Set

The SSD supports the SMART Command Set shown in the following table.

Table 15 SMART Commands

| Feature Field Values | Command |
|----------------------|-------------------------------------------------------------|
| D0h | SMART READ DATA |
| D1h | SMART READ ATTRIBUTE THRESHOLDS |
| D2h | SMART ENABLE/DISABLE ATTRIBUTE AUTOSAVE |
| D3h | SAVE ATTRIBUTE VALUES |
| D4h | SMART EXECUTE OFF-LINE IMMEDIATE |
| 00h* | Execute SMART Off-Line routine |
| 01h* | Execute SMART Short Self-test routine (Off-Line) |
| 02h* | Execute SMART Extended Self-test routine (Off-Line) |
| 03h* | Execute SMART Conveyance self-test routine in off-line mode |
| 04h* | Execute SMART Selective self-test routine in off-line mode |
| 7Fh* | Abort Off-Line routine |
| 81h* | Execute SMART Short Self-test routine (Captive) |
| 82h* | Execute SMART Extended Self-test routine (Captive) |
| 83h* | Execute SMART Conveyance self-test routine in captive mode |
| 84h* | Execute SMART Selective self-test routine in captive mode |
| D5h | SMART READ LOG |
| D6h | SMART WRITE LOG |
| D8h | SMART ENABLE OPERATIONS |
| D9h | SMART DISABLE OPERATIONS |
| DAh | SMART RETURN STATUS |
| *Low LBA values | |

6.2 SMART Attributes

The SSD supports the SMART attributes shown in the following table.

Table 16 SMART Attributes

| Name | Default Assignment | Description | Units |
|-------------------------------------|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| Raw Read Error Rate | 1 | A normalized rate of moderate to severe latency causing correctable errors. | Percentage |
| Reallocated Sector Count | 5 | Count of the number of blocks that have been reallocated, excluding pending sectors. | Counter |
| Power-On-Hours | 9 | Count of the lifetime power on hours in the Active or Idle ATA state. | Hours |
| Power Cycle Count | 12 | Count of the number of complete power up cycles. Excludes power mode state changes with power continuously applied. | Counter |
| Flash GB Erased | 100 | Count in GB of the lifetime erases of flash for all purposes. | Count in Giga bytes (2 ³⁰) |
| Lifetime PS4 Entry Count | 102 | Count of the number of times the PS4 power state is entered. | Counter |
| Lifetime PS3 Entry Count | 103 | Count of the number of times the PS3 power state is entered. | Counter |
| Grown Bad Block Count | 170 | Count of the number of retired flash blocks post manufacturing. | Counter |
| Program Fail Count | 171 | Count of the number of Flash Program failures. | Counter |
| Erase Fail Count | 172 | Count of the number of Flash Erase failures. | Counter |
| Average Program/Erase Count | 173 | Count of the average number of program/erase cycles on all good blocks. | Counter |
| Unexpected Power Loss Count | 174 | Count of the number of complete power loss events not preceded by a shutdown command. Excludes power mode state changes with power continuously applied. | Counter |
| Wear Range Delta | 177 | Difference between the most and least worn blocks with regards to the maximum rated P-E cycles (most-least)/max*100. | Percentage |
| SATA/PCIe Interface Downshift Count | 183 | Count of the number of times SATA interface rate reduction is negotiated. | Counter |
| Uncorrectable ECC Count | 187 | Count of the number of unsuccessful ECC recovery attempts where higher level recovery methods also failed. | Counter |
| Primary Temperature | 194 | Current, lifetime maximum and lifetime minimum temperature. | Celsius (Signed data) |
| RAISE ECC Correctable Count | 195 | Count of the number of times RAISE successfully recovered data. | Counter |
| Uncorrectable Read Error Count | 198 | Count of the number of times an uncorrectable error is returned to the host on a read command. | Counter |
| SATA R-Error (CRC) Error Count | 199 | Count of the number of detected SATA R-Errors experienced on the SATA receiver. | Counter |
| Drive Life Protection Status | 230 | Power fail protection available. | 100d, 64h unprotected SSD RO, 90d, 5Ah protected |

Table 16 SMART Attributes

| Name | Default Assignment | Description | Units |
|---------------------------|--------------------|------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|
| SSD Life Left | 231 | Approximate percent SSD life left, in terms of program/erase cycles or Flash blocks currently available for use. | Percentage |
| Available Reserved Space | 232 | Ratio of currently available internal reserved space to as built reserved space. | Percentage |
| Lifetime Writes to Flash | 233 | Sum in GB of the lifetime writes to flash for all purposes. | Sum in Giga bytes (2 [^] 30) |
| Lifetime Writes from Host | 241 | Sum in GB of the lifetime writes for all host write commands. | Sum in Giga bytes (2 [^] 30) |
| Lifetime Reads from Host | 242 | Sum in GB of the lifetime reads for all host read commands. | Sum in Giga bytes (2 [^] 30) |
| Free Space | 243 | Available user capacity in MB and percent of currently set user capacity. | Percentage User MB Free and percentage user space remaining |

6.3 SMART Trip

SMART trip (threshold exceeded condition) indicates impending degradation or fault condition. The host can issue a SMART return status command (B0h/DAh) to communicate the reliability status of the drive. The threshold-exceeded condition is also checked during drive self tests.

7. Standards and Reference Documents

Each Hard Drive and Solid State Drive ("device") has a product label that includes certifications that are applicable to that specific drive. The following information provides an overview of requirements that may be applicable to the drive.

7.1 Regulatory Model Numbers

The following regulatory model number represents all features and configurations within the series:

- STA010

7.2 Agency and Safety Certifications

7.2.1 Safety Certification

These products are certified to meet the requirements of UL/cUL 60950-1, EN 60950-1, and may also include, IEC 62368, UL 62368 and EN 62368.

7.2.2 Electromagnetic Compatibility

The device, as delivered, is designed for system integration and installation into a suitable enclosure prior to use. The drive is supplied as a subassembly and is not subject to Subpart B of Part 15 of the FCC Rules.

The design characteristics of the drive serve to minimize radiation when installed in an enclosure that provides reasonable shielding. The device is capable of meeting the Class B limits of the FCC Rules and Regulations of the Canadian Department of Communications when properly packaged; however, it is the user's responsibility to assure that the device meets the appropriate EMI requirements in their system.

7.2.3 Electromagnetic Susceptibility

The device as delivered is tested to meet susceptibility requirements in a representative enclosure. It is the responsibility of those integrating the drive within their systems to perform those tests required and design their system to ensure that equipment operating in the same system as the drive or external to the system does not adversely affect the performance of the device.

7.2.4 Electromagnetic Compliance

Seagate uses an independent laboratory to confirm compliance with the EMC directives and standards. The device was tested in a representative system for typical applications. Although the test system with this Seagate model complies with the directives/standards, we cannot guarantee that all systems will comply. The computer manufacturer or system integrator shall confirm EMC compliance and provide the appropriate marking for their product.

7.2.5 European Union (EU) CE Marking Requirements

Devices that display the CE mark comply with the European Union (EU) requirements specified in the Electromagnetic Compatibility Directive (2014/30/EU). Testing is performed to the levels specified by the product standards for Information Technology Equipment (ITE). Emission levels are defined by EN 55032:2012, Class B and the immunity levels are defined by EN 55024.

The devices also meet the requirements of The Low Voltage Directive (LVD) 2014/35/EU.

Although CE-marked Seagate devices comply with all relevant regulatory requirements and standards for the drives, Seagate cannot guarantee that all system-level products into which the devices are installed comply with all regulatory requirements and standards applicable to the system-level products. The device is designed for operation inside a properly designed system (e.g., enclosure designed for the device), with properly shielded I/O cable (if necessary) and terminators on all unused I/O ports. Computer manufacturers and system integrators should confirm EMC compliance and provide CE marking for the system-level products.

For compliance with the RoHS "Recast" Directive 2011/65/EU (RoHS 2), [see Section 7.3.1 on page 29](#).

7.2.6 Australian and New Zealand RCM Compliance Mark

If the device has the RCM marking, it complies with the Australia/New Zealand Standard AS/NZ CISPR32 and meets the Electromagnetic Compatibility (EMC) Framework requirements of the Australian Communications and Media Authority (ACMA).

7.2.7 Canada ICES-003

If the device has the ICES-003 Issue 6 marking, it complies with the requirements of ICES tested per ANSI C63.4-2014 or CAN/CSA-CISPR 22-10.

7.2.8 South Korean Certification Mark

If the device has the Korean Communications Commission (KCC) logo, they comply with KN32 and KN35.

| 기종별 | 사용자안내문 |
|------------------------|----------------------------------------------------------------------|
| B급 기기 (가정용 방송통신기자재) | 이 기기는 가정용(B급) 전자파적합기기로서 주로 가정에서 사용하는 것을 목적으로 하며, 모든 지역에서 사용할 수 있습니다. |

7.2.9 Morocco Commodity Mark

Seagate drives are tested for compliance and comply with the European Union (EU) Electromagnetic Compatibility (EMC) Directive 2014/30/EU and the Low Voltage Directive (LVD) 2014/35/EU. Accordingly, the drives also meet the requirements of Morocco's Order of the Minister of Industry, Trade, Investment and Digital Economy No. 2574-14 of 29 Ramadan 1436 (16 July 2015) on electromagnetic compatibility of equipment.

For devices with the Morocco Mark, Seagate has added the Moroccan Commodity Mark to the devices provided to the OEM for the sale of Customer Kits produced by our OEM customers that are intended to be incorporated into the OEM's finished system-level product by an end user. The Customer Kits are considered 'devices' under Morocco's Order of the Minister of Industry, Trade, Investment and Digital Economy No. 2574-14 of 29 Ramadan 1436 (16 July 2015) on electromagnetic compatibility of equipment.

7.2.10 Taiwanese BSMI

Devices with the Taiwanese certification mark comply with Chinese National Standard, CNS13438 (2006.6) and CNS 15663 (2013.7).

For compliance with the Taiwan Bureau of Standards, Metrology and Inspection's (BSMI) RoHS requirements, [see Section 7.3.3 on page 31](#).

7.3 Environmental Protection

Seagate designs its products to meet environmental protection requirements worldwide, including regulations restricting certain chemical substances.

7.3.1 European Union Restriction of Hazardous Substance Law

7.3.1.1 Restriction of Hazardous Substances in Electrical and Electronic Equipment

Seagate devices are designed to be compliant with the European Union RoHS "Recast" Directive 2011/65/EU (RoHS 2) as amended by Directive (EU) 2015/863. The RoHS2 restricts the use of certain hazardous substances such as Lead, Cadmium, Mercury, Hexavalent Chromium, Polybrominated Biphenyls (PBB) and Polybrominated Diphenyl Ether (PBDE), BisBis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP), and Diisobutyl phthalate (DIBP) in electrical and electronic equipment (EEE).

7.3.1.2 Substances of Very High Concern (SVHC)

The European Union REACH (Registration, Evaluation, Authorization and Restriction of Chemicals) Regulation (EC) 1907/2006 regulates chemicals shipped into and used in Europe. A number of parts and materials in Seagate products are procured from external suppliers. We rely on the representations of our suppliers regarding the presence of REACH substances in these articles and materials. Our supplier contracts require compliance with our chemical substance restrictions, and our suppliers document their compliance with our requirements by providing full-disclosure material content declarations that disclose inclusion of any REACH-regulated substance in such articles or materials. Product-specific REACH declarations are available upon request through your Seagate Sales Representative.

7.3.2 China Requirements —China RoHS 2



China RoHS 2 refers to the Ministry of Industry and Information Technology Order No. 32, effective July 1, 2016, titled Management Methods for the Restriction of the Use of Hazardous Substances in Electrical and Electronic Products. To comply with China RoHS 2, Seagate determined this product's Environmental Protection Use Period (EPUP) to be 20 years in accordance with the *Marking for the Restricted Use of Hazardous Substances in Electronic and Electrical Products*, SJT 11364-2014.

Table 17 China - Hazardous Substances

| 部件名称 Part Name | 有害物质 Hazardous Substances | | | | | |
|-------------------|------------------------------|-----------|-----------|----------------------------|---------------|-----------------|
| | 铅 (Pb) | 汞 (Hg) | 镉 (Cd) | 六价铬 (Cr ⁺⁶) | 多溴联苯 (PBB) | 多溴二苯醚 (PBDE) |
| 印刷电路板组装 PCBA | X | O | O | O | O | O |
| 机壳 Chassis | X | O | O | O | O | O |

本表格依据 SJ/T 11364 的规定编制。
This table is prepared in accordance with the provisions of SJ/T 11364-2014

O: 表示该有害物质在该部件所有均质材料中的含量均在 GB/T 26572 规定的限量要求以下。
O: Indicates that the hazardous substance contained in all of the homogeneous materials for this part is below the limit requirement of GB/T26572.

X: 表示该有害物质至少在该部件的某一均质材料中的含量超出 GB/T 26572 规定的限量要求。
X: Indicates that the hazardous substance contained in at least one of the homogeneous materials used for this part is above the limit requirement of GB/T26572.

7.3.3 Taiwan Requirements — Taiwan RoHS

Taiwan RoHS refers to the Taiwan Bureau of Standards, Metrology and Inspection's (BSMI) requirements in standard CNS 15663, Guidance to reduction of the restricted chemical substances in electrical and electronic equipment. Seagate products must comply with the "Marking of presence" requirements in Section 5 of CNS 15663, effective January 1, 2018. This product is Taiwan RoHS compliant.

The following table meets the Section 5 "Marking of presence" requirements.

Table 18 Taiwan - Restricted Substances

| 設備名稱：固態硬碟， Equipment Name: 2.5 inch SSDs | | 型號（型式） Type Designation (Type) | | | | |
|---------------------------------------------|------------------------------------------------------------|-----------------------------------|----------------------|------------------------------------------------------|----------------------------------------------|------------------------------------------------------|
| 單元 Unit | 限用物質及其化學符號 Restricted Substance and its chemical symbol | | | | | |
| | 鉛 Lead (Pb) | 汞 Mercury (Hg) | 鎘 Cadmium (Cd) | 六價鉻 Hexavalent Chromium (Cr ⁺⁶) | 多溴聯苯 Polybrominated biphenyls (PBB) | 多溴二苯醚 Polybrominated diphenyl ethers (PBDE) |
| 快閃記憶體 Flash Memory | ○ | ○ | ○ | ○ | ○ | ○ |
| 連接器 Connector | ○ | ○ | ○ | ○ | ○ | ○ |
| 外殼 Product Cover | ○ | ○ | ○ | ○ | ○ | ○ |
| 印刷電路板總成 PCB Assembly | — | ○ | ○ | ○ | ○ | ○ |

備考1. "超出0.1 wt %" 及 "超出0.01 wt %" 係指限用物質之百分比含量超出百分比含量基準值。
Note 1: "Exceeding 0.1 wt %" and "exceeding 0.01 wt %" indicate that the percentage content of the restricted substance exceeds the reference percentage value of presence condition.

備考2. "○" 係指該項限用物質之百分比含量未超出百分比含量基準值。
Note 2. "O" indicates that the percentage content of the restricted substance does not exceed the percentage of reference value of presence.

備考3. "—" 係指該項限用物質為排除項目。
Note 3. "—" indicates that the restricted substance corresponds to the exemption.



Seagate Technology LLC

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000

ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888

EUROPE, MIDDLE EAST, AND AFRICA Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

Publication Number: 100834145, Rev. A

July 2018